

LEWMAR®




LEWMAR AISI316 stainless steel portlight

AISI 316



Fitted with friction hinges and quick-locking handles. The handles and hinges leave the lens clear of obstructions, giving it an uncluttered view and clean modern look.. **CE-approved for areas 1B and 2A.**
To be installed on 9-mm to 30-mm thick surfaces. Supplied with 20 x M5 studs for 17/2-mm thick surfaces. ABS internal trimming ring (chromed for size 8) and removable flyscreen.

Code	Model	outside mm			Cut size mm		kg	Acrylic glass thickness mm
		X	Y	Thickness	X1	Y1		
19.430.80	8	196	452	10	176	432	1.9	10
19.430.82	1 RE	191	367	10	171	347	1.7	10
19.430.84	7 RE	191	425	10	171	405	1.9	10



LEWMAR®




LEWMAR AISI316 stainless steel round portlight

AISI 316



Supplied with trimming ring made of chromed ABS, mounting screws and smoked lens. Fast and simple installation by means of a ring nut with threaded bores, to be made by a single operator. 180° opening. **CE-approved for category B Area 1.**

Code	Outside mm	Cut size mm	Light mm	For hulls with thickness
19.431.25	250	230	160	8 to 24 mm
19.431.30	300	250	200	8 to 24 mm



LEWMAR®



LEWMAR ventilator

Made of reinforced plastic, it exchanges air and prevents water seepage. It can be mounted onto the hatch glass or on the deck. Universal model complying with the CE ISO 12216:2003 standards.

Code	External Ø mm	Recess bore mm
19.041.01	170	76

