


Inspection hatch with very sturdy anti-slip walking surface, UNI EN ISO 12216:2004

Splash-proof cover locking with neoprene gasket. Flush-mount. It may be used as hatch for lockers, fishing tanks, storeroom hatch and bulkhead hatch. **160° opening**. It can be installed on any sports craft, boat design category A, B, C, and D, area II a, III, IV, watertightness degree 2. It can be installed on any sports craft, boat design category A, B, C, and D, area II a, III, IV, watertightness degree 2.

white	grey	Outside mm	Inside mm	Optional immediate installation lock kit
20.301.00	20.301.60	280x380	180x280	20.093.00
20.302.00	20.302.60	345x595	250x500	20.093.00

CE APPROVED
based on
UNI EN ISO 12216:2004



20.093.00 Ready installation lock kit OPTIONAL



Inspection hatch with removable front lid

OSCULATI

Very sturdy anti-skid surface; **splash-proof** lid closure with neoprene seal; flush mounting; they can be used as hatches for lockers, fishing containers or as boxroom hatches or bayonet front bulkheads; removable front for easy access. Ideal for installation on dashboard with nearby steering bench.

white	Cream RAL 9001	grey	Black	Outside mm	Inside mm	Optional immediate installation lock kit
20.302.20	20.302.21	-	20.302.23	305 x 355	225 x 275	-
20.302.30	20.302.31	20.302.32	20.302.33	375 x 375	295 x 295	-
20.302.40	-	-	-	350 x 600	250 x 500	20.093.00



PUSH PULL inspection hatch

EASY OPEN

Opening and closing with flush handle and snap closure. Seal of the lid with neoprene gasket. Opening at 175°.

white	Outside mm	Inside mm	Cut size mm	Lock kit OPTIONAL
20.303.00	380x280	295x198	310x210	20.094.00
20.305.00	405x375	320x290	330x300	20.094.00
20.306.00	520x465	430x375	445x390	20.094.00
20.304.00	600x350	513x265	530x280	20.094.00



20.094.00 lock kit



20.304.00



20.306.00



20.305.00



20.303.00

OSCULATI