

Self-inflatable personal floatation devices complying with EN ISO 12402-3 standards

OSCULATI


▲ 22.409.23/27

Security self-inflating lifejacket 150 N (EN ISO 12402-3) with HAMMAR hydrostatic inflation



Fitted with **safety harness complying with ISO 12401 standards**. The HAMMAR MA1 hydrostatic automatic inflator prevents the jacket from unwanted inflation, as it happens with traditional inflating systems that activate when coming into contact with water. The HAMMAR system activates only with hydrostatic pressure (immersion of at least 15 cm in water). Model for adults with thigh strap.

Code	Activation	Colour	Cylinder + Hammar MA1
22.395.00	Hammar automatic	red	22.395.10

Hammar Activator - 33g cylinder

22.409.23 MED-approved automatic activation emergency light, mandatory on every belt for navigation beyond 6 miles from the coast.

22.409.27 Light attachment clip 22.409.23 on the mouthpiece of life belts.

OSCULATI


▲ 22.409.23/27

Professional self-inflatable lifejacket 180N (EN ISO 12402-3)



Ergonomic shape with collar and quick-release buckles, safety thigh straps. Two attachments for safety belts, **ISO 12401 certified**. Automatic or manual activation, with a transparent window allowing to check the efficiency of the fastening device. Adult model.

Code	Colour	Cylinder + spare valve	
		for lifebuoys produced until 04/19	for lifebuoys produced from 5/19
22.397.00	Black	22.397.10	22.397.11

22.409.23 MED-approved automatic activation emergency light, mandatory on every belt for navigation beyond 6 miles from the coast.

22.409.27 Light attachment clip 22.409.23 on the mouthpiece of life belts.

OSCULATI


▲ 22.394.00



▲ 22.394.10



▲ 22.409.23/27

Sail Pro self-inflating lifejacket - 180N (EN ISO 12402-3)



Hammar hydrostatic automatic inflation (this system prevents accidental inflation); Integrated safety belt **ISO 12401 certified**; 25% more compact than traditional self-inflating belts: easier movements; Opening of the casing via automatic zipper: less weight, less bulk, faster opening and closing of the casing compared to the tear-off and safety thigh strap system. Combined with the automatic signalling light 22.409.23, it becomes mandatory as onboard equipment beyond 6 nautical miles from the coast.

Code	Activation	Exterior color
22.394.00	Hammar automatic	Black



22.394.10 Fluo water/wind spray hood **OPTIONAL**.

22.395.11 38-g spray can + Hammar MA1

22.409.23 Automatic electronic signalling.

22.409.23 MED-approved automatic activation emergency light, mandatory on every belt for navigation beyond 6 miles from the coast.

22.409.27 Light attachment clip 22.409.23 on the mouthpiece of life belts.

OSCULATI


▲ 22.393.00



▲ 22.394.10



▲ 22.409.23/27



Premium self-inflatable lifejacket - 300 N (EN ISO 12402-2)



Designed for the toughest conditions. 300N buoyancy for utmost safety even when wearing boots, waterproof garments, etc. and allowing a very fast body rotation. HAMMAR hydrostatic activation that prevents unwanted inflation (possible with traditional activation systems). **OPTIONAL ISO 12402-8 Fluo spray hood** (22.394.10). Safety harness **complying with ISO 12401 standards**. Comfortable padded collar. Fitted with thigh strap.

Code	Activation	Colour	Replacement cartridge (60g) + HAMMAR MA 1 valve
22.393.00	Hammar automatic	Black	22.393.01



22.394.10 Water-/wind spray hood

22.409.23 Automatic electronic signalling.

22.409.23 MED-approved automatic activation emergency light, mandatory on every belt for navigation beyond 6 miles from the coast.

22.409.27 Light attachment clip 22.409.23 on the mouthpiece of life belts.