




▲ 22.409.23



▲ 22.409.27



Automatic electronic signalling device for lifejackets



MED approved. Automatic activation upon water contact. Functions: fast flashing, steady light, SOS, OFF. To be paired with a 150N life jacket as onboard equipment within 12 miles.

Code	Activation	↔ mm	Optional fastening clip
22.409.23	Automatic in contact with water	62x28x31.5	22.409.27 * New

* To be attached to the mouthpiece of the self-inflating life belts.



OSCULATI



▲ HAMMAR



▲ UML 5



▲ 22.401.10

Service kit for self-inflatable lifejackets

Bottle and universal spare valve kit for self-inflatable lifejackets

Code	Cylinder	Actuator	Use
22.401.10	33	no	150 newton manual
22.398.14	33	UML-5	150 newton automatic
22.395.10	33	HAMMAR	150 newton automatic
22.397.10	38	UML-5	180 newton automatic
22.397.11	38	UML Pro Sensor Elite	180 newton automatic
22.399.15	24	UML-5	Baby automatic
22.395.11	38	HAMMAR	180 newton automatic
22.397.60	60	UML-5	MOB, Dan buoy, etc.
22.294.01	60	UML-5	275 Newton automatic

MED-approved lifejackets



▲ 22.411.01



▲ 22.411.02



▲ 22.411.03



WORLDLIFE 8 MED-approved lifejacket, IMO resolution MSC.200(80)

With RINA approval for the commercial maritime sector. Manufactured in accordance with the new IMO regulation MSC.200(80). In combination with the automatic signal light 22.409.23, it becomes mandatory as onboard equipment beyond 6 miles from the coast.

Code	Colour	Size	Type
22.411.01	 red	over 40 kg	adults
22.411.02	 red	16 to 43 kg	youths
22.411.03	 red	up to 15 kg	kids