

## PVC tender

**OSCULATI**

### Rubber dinghy with cross slat bottom

Folding version with cross slats on the flat bottom. Once folded, it is the most compact available model for those having limited stowage space. It comes with oars, inflator, repair kit and carrying bag.

Code	Type	Length m	Width m	No. of people	Max power HP	Tubular Ø cm	Air chambers	Max load kg.	↔ deflated cm	kg
22.620.18	185	1.85	1.31	1+1	2.5	36	2	200	96x56x32	12*
22.620.21	210	2.10	1.17	2	3.5	34	2	250	96x56x32	20*
22.620.24	240	2.40	1.52	3	6	42	3	450	111x64x32	25*

\* Net weight of detachable accessories



### Dinghy with high-stiffness inflatable deck floor

This technology combines easy stowage to excellent seaworthiness. Fold after use like a rigid slat dinghy. Ideal in case of limited stowage space. It comes with oars, inflator, repair kit and carrying bag. At a length of 2.5 m, it is CE certified according to ISO 6185

Code	Type	Length m	Width m	No. of people	Max power HP	Tubular Ø cm	Air chambers	Max load kg.	↔ deflated cm	kg
22.630.25	240	2.4	1.37	2	4	36	3+1	350	101x60x31	23*
22.630.28	270	2.7	1.5	3+1	10	42	3+1	484	111x61x35	33*
22.630.32	310	3.1	1.51	4+1	15	42	3+1	566	111x61x38	35*

\* Net weight of detachable accessories

