

Foot-operated controller with solenoid

It includes **rubber** pedal and **mirror-polished stainless steel** watertight ring nut.
Can operate with foot pedal, manual controls, and panel controls.



Pedal color		V	W	They can also operate with		
black	red			Footboard	manual controls	panel controls
02.338.00NE	02.338.00RO	12	2000	02.342.01; 02.342.02; 02.342.03; 02.342.04	02.339.00	02.341.00; 02.341.20
02.338.01NE	02.338.01RO	24	2000	02.342.01; 02.342.02; 02.342.03; 02.342.04	02.339.00	02.341.00; 02.341.20

Solenoid for winch

Can operate with foot pedal, manual controls, and panel controls.

Code	It works with			V	W	 mm
	electronic pedals	manual controls	panel controls			
02.456.12	02.342.01; 02.342.02; 02.342.03; 02.342.04	02.339.00	02.341.00	12	1000	78x51



MZ ELECTRONIC Control Box - contactors/inverters

Power units for anchor winch controls with 3 or 4 wire motors or permanent magnets. Protection grade IP56. Compatible with all foot, hand, or portable controls.

Code	V	For motors max W	For motors with No of poles	 mm	Corresponding item		
					LEWMAR	QUICK	MZ ELECTRONIC
02.316.01	12	700	2/4	114x52x88	68000320	T6415-12	MZ2090/L
02.316.02	12	1000/1500	2/4	148x60x95	68000320	T6415-12	MZ2130/H
02.316.03	24	500/1500	2/4	148x60x95	68000321	-	MZ2130/I
02.316.06	12	1500/4000	2/4	148x70x120	-	T6415-12	MZIC20133
02.316.07	24	1500/3000	2/4	148x70x120	-	T6415-24	MZIC20134
02.316.05	24	3000/3500	2/4	160x100x150	68000321	T6415-24	MZIC20123
02.317.01	12	500	3	114x52x88	68000937	T6315-12	MZ2100/M
02.317.02	12	1000/1500	3	148x60x95	68000937/68000318	T6315-12	MZ2150/C
02.317.03	24	500/1400	3	148x60x95	68000938/68000319	T6315-24	MZ2150/D
02.317.04	12	1700/2300	3	130x70x120	68000318	T6315-12	MZ2150PA/C
02.316.04	24	1500/2300	3	148x60x95	68000319	T6315-24	MZ2150PA/D



Windlass or bow thruster control panel with safety switch

Version with Airpax toggle switch. Disconnects power in case of accidental overload via the magneto-hydraulic safety switch. Essential for protecting the motor. Supports a load of 200% for 10 seconds. Complete with a 12V red indicator light.

Code	A	Panel mm	Recommended for windlasses W	
			12V	24V
02.340.00	100	80x60	700/1200	1000/2000
02.340.01	50	80x60	400/500	700/1000

OSCOLATI

