



VDO spare propeller

Code	Description
27.270.05	Spare propeller for 50 knots (2192)(2192)

Accessories for instruments



Instrument sensors


Rudder angle sensor. It matches 27.320.17 / 27.321.17 / 27.322.17 and VDO instruments.

Code	Resistance	V	Function
27.330.01	190 Ω	12/24	matches 1 instrument
27.330.02 New	190 Ω	12/24	matches 2 instruments



27.330.10 *Optional connection bar.*

Universal pilot pipe



Code 27.315.00

Suitable for any water pressure speedometer; can be used up to 80 MPH, made of white nylon.

Special high pressure hose, designed for water pressure speedometers



Made of PVC, universal.

Code	Rolls of
27.316.00	25 m

NMEA 2000 connector

IP68

Cables and connectors to create an onboard NMEA 2000 network. Sturdy IP68 connectors for use in marine environment.

Code	Description	Length m	Colour
27.363.02	TEE (2 female/ 1 male)	-	grey
27.364.01	Male terminal connector	-	Black
27.364.02	Female terminal connector	-	Black
27.363.15	Power cord to power the system via a TEE terminal	5	yellow

Level indicator + sensors

Fuel level indicator



Waterproof, fitted with floater and FUEL symbol. 240-33 Ω frequency. For 12V installations.

Code	Ø mm	For tanks with depth in mm
27.160.00	52	130/660

Universal Gauge



TANK letter symbol (suitable for any type of liquid).

Resistance		Ø mm
10-180 Ω	240-33 Ω	
27.159.00	27.170.00	52

Universal floater for fuel level gauge

5-hole international flange. 70-mm Ø.

Resistance 240-33 Ohms (Teleflex, Faria USA, Vetus, S. Giorgio Sein, Beede, Medalion)	Resistance 10-180 Ohms (VDO, Yazaki, Faria Europa, Uflex, Guardian)	For tanks with depth in mm
27.160.01	27.160.02	130/660

Universal lever float for fuel level

Metal parts made of **stainless steel**. Scratch-proof, made of **ceramic** with **platinum** contact (4 million movements guaranteed). Adjustable for tanks with height of 150-600. Mobile rod delay patented system, neutralizes the pitch/roll effect.

Code	Resistance
27.160.05	240-33
27.160.06	10-180