


Waterproof magnetothermal protection switch for winch, bow thruster and gangway

HEAVY DUTY

Resettable, it can be released by means of a special lever. It is both a fuse and a switch.
Made in compliance with the USA SAE J1171 / SAE J1625 standards.
Voltage allowed: max 48 V, operating temperature: -32° + 92°.
With 3/8" electrical terminals. IP67 Weatherproof.

Code	Max load A
02.752.50	50
02.752.70	70
02.752.10	100
02.752.15	150
02.752.20	200
02.752.25	250




Waterproof magnetothermal circuit breaker for winch and bow thruster

HEAVY DUTY

Automatic resetting version.
Made in compliance with the SAE J1625 / SAE 1171 standards.
Operating temperature: -32° + 92°.
With 3/8" electrical terminals. IP67 Weatherproof.

Code	Max load A
02.753.60	60
02.753.80	80
02.753.12	120
02.753.15	150
02.753.20	200
02.753.25	250



Anchor Lube oil for windlasses

Lubricant with a 220 ISO viscosity grade. Designed for windlasses of any brand.

Code	Package l
02.294.00	1



Rope/chain sets for windlasses

Manufactured with a high-tensile white 3-strand rope and **stainless steel false link** terminal suitable for connecting to the winch chain.

Code	Ø mm	Length m	Gypsy Ø mm	Chain link Ø mm	For windlasses
02.636.01	10	35	6	6	Manual mooring, Lofrans: Project x1; Italwinch 02.407.01
02.636.02	12	35	6	6	Lewmar: Pro-series 1000, V-700, V1, V2 Lofrans: Project x1, Dorado 500W, Marlin; Lewmar CPX0; Italwinch Ray; Italwinch RayLux
02.834.00	14	35	8-10	8	Lewmar: Pro-series 1000, V1, V2, V3, V4 Lofrans: Project x1-x2-x3, Project 1000-1500, Dorado 700W, Clipper 700-1000; Italwinch Thunder, Italwinch ThunderLux
02.636.05	16	40	10	10	Lewmar: Pro-series 1000, V3, V4, V5 Lofrans: Project x2-x3, Project 1000-1500, Clipper 1000; Italwinch Thunder Lux Ø 16



LEWMAR clutch lever for windlasses

Universal for all Lewmar winches, in black plastic.

Code	Description
02.531.90	Dual clutch lever: universal + V700.

LEWMAR®

