

RAYMARINE instruments

Raymarine



29.592.01



29.593.01



29.592.03



29.592.20

RAYMARINE i50 / i60 instruments

Designed to be combined with the new Raymarine e-Series and c-Series multifunction displays.

- Large keys for easy reading
- Red background for better night vision
- SeaTalk and SeaTalkng interface
- NMEA2000 interface (compatible)
- Integrated transducer interface
- Dimensions: 110mm x 115mm (same as ST60+)
- Large keys for easier use during navigation
- Multiple data sources to avoid data clashes
- Front mounting for very easy installation.
- The package includes a front panel to make these instruments similar to the eS series.

| Code | Model | Description |
|------------|---|--|
| 29.592.01 | i50 | Speed display (digital) |
| 29.592.02* | i50 | Depth display (digital) |
| 29.592.03 | i50 | i50 Tridata display (digital) |
| 29.593.01 | i60 | i60 Wind display (analogic) |
| 29.592.20 | complete package including instruments, transducers and connection cables | |
| | | Display i50 Speed + i50 Depth + i60 Wind + Speed transducers (St. 900) + Depth (M78713-PZ) + Wind (E22078) |

* 80-m max range.

i70 multipurpose RAYMARINE instrument


Large 4" LCD display, easy to read and perfectly visible from any angle and distance. The i70 instrument can be customized depending on the boat type. It offers traditional analogical screens as well as details about engine and fuel or information as AIS repeater: the i70 Raymarine can display all required data.

Technical data:

4" LCD display with 160° visual angles, 43-mm number in full screen mode. Anti-reflection treatment. Light House interface. AIS repeater.

Data supported: wind, speed, depth, tridata, engine (NMEA 2000), environment (NMEA 2000), fuel (NMEA 2000) and navigation.

To be connected to traditional transducers by adding a POD or to smart transducers.



| Code | Model | Power supply | Display Size | Resolution |
|----------------------|---|---------------|--------------|----------------|
| 29.603.01 | i70s | 12 V via STNG | LCD 4,1" | 320x240 (QVGA) |
| 29.603.10 New | i70s System Pack (Colour Instrument with Wind Transducer and DST, iTC-5, 3m BB cable, power cable, 5-way connector, 2 BB terminals) | 12 V via STNG | LCD 4,1" | 320x240 (QVGA) |

Transducers and sensors for Raymarine instruments

| Code | Reference | Description | ST40 / i40 | ST60 / i50 / i60s | i70 |
|----------------------|------------|--|------------|-------------------|-------------------|
| 29.590.13 | E26009 | Depth thru-hull plastic transducer (9-m cable) | • | • | - |
| 29.600.13 | M78713-PZ | Depth plastic thru-hull (P19) | • | • | • (with POD iTC5) |
| 29.600.19 New | A22154 | Thru-hull plastic transducer (DST800 - analogue) | • | • | • (with POD iTC5) |
| 29.600.17 | E26001-PZ | Depth adjustable internal transduction (cable 12m) | • | • | • (with POD iTC5) |
| 29.590.12 | E26008 | Thru-hull speed/temperature plastic transducer (9-m cable) - Short | • | • | - |
| 29.600.14 New | E70673 | Thru-hull transducer | • | • | • (with POD iTC5) |
| 29.600.21 | Z195 | Wind Rotavecta transducer (20-m cable) | • | • | • (with POD iTC5) |
| 29.600.20 | E22078 | Wind standard mast head transducer (30-m cable) | - | • | • (with POD iTC5) |
| 29.600.42 | E70010 | Multiple POD converter for 5 iTC5 transducers | - | - | • |
| 29.600.25 | T120 | Wind wireless transducer | - | •* | •* |
| 29.600.26 New | E70670 RSW | Smart Performance Wind Transducer, short arm with 30m cable | - | - | •** |

* Compatible via gateway interface 29.602.15

** Compatible with i70 and Axiom s iTC compatible with i70 and Axiom without the need for the iTC5 converter

