

## Accessories for electronic equipment

### Noise suppressor

**Code** 29.451.20

For installation in the power lead to depth sounders, GPS, Plotters, radio-telephone, etc. It eliminates interference from energy-hungry alternator or onboard instruments (anchor windlasses, radars, etc) and protects instruments against power discharges; 12 V, 60 watt (5Amp), intervention time 5 nanos, peak power 4500 Amp, dissipated energy 45 joules.



### GLOMEX deck nylon fairlead

**Code** 29.140.00

Universal for one two cables, **the connector is also able to pass through.**



### GROUNDPLATE mass plates equipped with special nuts and bolts

Made of **porous bronze**, ideal for achieving an appropriate mass while installing Loran, GPS, Satellites, radio-telephones SSB and help cut-down radio interferences.

Code	Type	Equivalent to copper mass m <sup>2</sup>	l mm
29.630.01	Standard	1.15	155x51x13
29.630.00	MEDIUM	2	205x64x13
29.630.02	Giant	3.45	300x80x13



## Portable and panel depth sounder

### VEETHREE dashboard recessed echosounder

It reads from 0,7 to 61 meters up to 101 km/h (63 mph). LCD polarised display. Meters or feet scale. Min. and max. depth alarm (acoustic and optical). 250W max power. 200-khz stern transducer with 9-m cord. Depth calibration depending on the hull immersion (keel offset).

Code	Dial	Ring
29.230.31	Black	Black
29.230.30	white	Polished S.S.



▲ 29.230.30



▲ 29.230.31

### NORCROSS portable depth-sounder with built-in transducer

Easy to use: **rest** it on the boat bottom (fiberglass, aluminium, rubber, etc.) from the inside or put it into water for depth reading.

Technical data:

- Range 0.6-72 m (possibility to select 2-240 foot scale).
- Display of water and air instantaneous temperature.
- Smart DepthTrax™ transducer to prevent false signals.
- LCD display.
- Sensitivity gain automatic adjustment.
- Shoot-Thru™ technology: the signal passes through the bottom or the ice or putting it into the water.
- Float with shock resistant rubber cover.
- Waterproof up to 50 metres under water (it can also be used by **scuba divers** since it's IPX8 watertight).
- Power: 1 x 9V (6LR61) alkaline battery.

Code	l mm
29.028.02	200x60

