

360° lights for signalling buoys, nets, wharfs, etc.

LED signalling lights for signalling buoys or fishing nets

**LED** Made in compliance with the Official Gazette No 112 dated 30/04/2011 Art. 13-16-17. CE 1224/2009 regulations. Fitted with automatic twilight switching. Equipped with No. 2 LED electronic circuits to provide white and yellow light. Batteries not included.

Code	Power supply (standard batteries)	Lens colour	Flash	Minimum visibility	Duration	↔ mm
30.592.01	2xUM-1	white + yellow	12 / min	3 miles	25 nights	255x55
30.592.06	2xUM-1	white + yellow	12 / min	3.5 miles	60 nights	210x60



Signalling buoy

Ready to fit signalling lights.

Code	Volume litres	Buoyancy kg	Ø mm	H mm	Colour	Matchable signal light
33.176.04	15	13.5	320	800	yellow	30.596.01/03/04
33.176.05	50	50	500	1030	yellow	30.596.01/03/04



LED warning light

**IP67**

It signals obstacles, signalling buoys, wharves, harbour entrances, etc. Fitted with seagull scarer. Powered by lithium batteries charged via a mini solar panel. The light comes with a bracket and clamp for 18/32-mm tubes; UV-, oil- and corrosion-resistant; CE type-approved. Switching on:  
1 - Automatic twilight switching with flashing mode activation (4 flashes in sequence x 52 cycles/minute).  
2 - 30-m reach radio remote control.  
3 - Manual.

**VERSION A**  
- White fixed light.  
- White single FLASH.  
- White flashing light (4 FLASHES in sequence)  
- White SOS light.  
- Off.

**VERSION B**  
- fixed coloured light (green);  
- FLASH coloured angle (green);  
- Gradual FLASH (green);  
- White SOS light.  
- White fixed light.  
- Off.

Dimensions: 115x73 mm; weight: 225 gr + 120 gr (bracket).



Code	Light	Version	Visibility in nautical miles		Battery life hours at 100% charge		
			Flash	Fixed Light	Flash	S.O.S	Fixed Light
30.596.01	white	A	1.5	2.0	300	30	12
30.596.04	green	B	3.4	2.0	150	30	12