


OSCULATI

Extinguisher compartment with door

Made of **white polypropylene** with **clear UV resistant polycarbonate** hatch, snap-in closure for ANAF 1-kg fire extinguishers. Watertight, high-quality finish, white colour. Supplied with special brackets and self-blocking strap for perfect fastening of the extinguisher.

Code	Exterior frame mm	Cutout dimension mm	Depth below frame mm
31.429.00	183x364	140x321	75


OSCULATI


Extinguisher compartment snap in

**SNAP IN / A
SCATTO**

Created for ANAF extinguisher (1kg). You have only to press it into the box, without any type of hook.

Code	Material	↔ outside mm	Depth mm
31.428.01	White ABS	150x408	81

Gas and CO detector



Carbon monoxide detector

Very compact battery-powered detector with acoustic alarm. Battery life guaranteed for 10 years from the manufacture date.

Code	Description	Sound alarm dB	↔ mm
31.300.00	Battery-powered detector (10-year life)	85 at 3 m	Ø40 x 38

XINTEX


XINTEX G-2B-R gas/petrol fume detector

Fitted with **2 sensors** to locate in the bilge. 68-dBA acoustic alarm + red LED warning light. TEST-SILENCE control push button. Supplied with 2 x 6-m cables.

Code	V	Maximum current consumption mA	↔ panel mm	Extension cable 6 m OPTIONAL	Replacement sensor
29.787.01	10/30	150	67x67	29.787.11	29.787.12

XINTEX


XINTEX P2BS propane fume detector

Fitted with **2 sensors** to be positioned where needed and a **solenoid valve**. A LED will light and a 68-dB alarm will sound in case of leaks; it automatically closes the solenoid valve.

Code	V	Maximum current consumption mA	↔ panel mm	Extension cable 6 m OPTIONAL	Replacement sensor
29.788.01	10/30	780	67x67	29.787.11	29.787.12

XINTEX


XINTEX CMD-6 carbon monoxide alarm

Internal-combustion engines produce carbon monoxide. A faulty current generator might release exhaust emissions in the bilge, which is extremely dangerous for people on the boat.

The CMD-6 microprocessor-controlled alarm detects the levels of CO. The TWA (Time-Weighted Average) CO measurements process constantly monitors all CO levels (concentration, time and temperature) to calculate the precise alarm point depending on the COHb %.

- Multiple detectors can be interconnected.
- Relay module included for generator shutdown.

Code	V	Alarm point	Sound Alarm DBA	↔ mm
29.782.02	12/24	10% COHb	85 at 3 m	89x89x31
29.782.04	independent with lithium/ion battery (7 year end of life)	10% COHb	85 at 3 m	89x89x31