#### Aluminium telescopic boat hook

White nylon hook, anodized aluminium pole and white polished rubber handle; very light, it floats, adjustable in all positions with its special cam.

Code	Minimum/maximum length in cm	Tube Ø mm
34.459.00	100/200	25/30
34.459.02*	60/100	25/30

Suitable for safety kits.



### COSCULATI





## TRI-TELESCOPIC boat hook

Made of **mirror polished anodized aluminium**, with nylon hook and handle; very sturdy, made with 3 sturdy concentric tubes; can be adjusted in any position with its cam.

Code	Minimum/maximum length in cm	Tube Ø mm
34.460.00	115/285	25/30/35










### Professional telescopic boat hook

Made of **anodized aluminium**, natural finish (**includes hook**). Its rotation locking device enables fast locking at any point, very sturdy.

Code	Version	Minimum/maximum length in cm	Tube Ø mm
34.915.41	Bi-telescopic (2 tubes)	120/209	25/29
34.915.42	tri-telescopic (3 poles)	105/245	25/29/32



## **OSCULATI**



#### Professional telescopic boat hook with roller

Made of anodized aluminium, includes hook.

Code	Version	Minimum/maximum length in cm	Tube Ø mm
34.916.41	Bi-telescopic	120/209	25/29
34.916.42	Tri-telescopic	105/245	25/29/32



# **OSCULATI**



### Professional boat hook with rubber head

 $\label{lem:matter} {\it Made of natural anodized aluminium with anti-skid bi-component technolopolymer hook. Quick lock in all positions via rotation.}$ 

Code	Version	From min to max cm	L min-max cm	Tube Ø mm
34.917.42	tri-telescopic (3 poles)	94-244	110-260	25/29/32
34.917.43	tri-telescopic (3 poles)	134-366	150-382	25/29/32



