

## Push to close latches

### Pull latches / hatch lifting device

Made of mirror polished **precision-cast AISI 316 stainless steel**; using a pressure lock, the handle can stay opened or closed.


Code	For doors with thickness mm	Bore Ø mm	Flange Ø mm
38.147.50	3/19	51	62



### Plastic flush pull latches

Made of **white nylon**, fitted with **stainless steel** lock stopper and two 2 mm stoppers.

Code	Version	Colour	Recess Ø mm	External Ø mm	Inner size mm	Accepts thicknesses mm
38.147.00	without lock	white	49.6	61.4	38.8	from 7 to 18
38.147.01	without lock	Black	49.6	61.4	38.8	from 7 to 18
38.147.20	With lock	white	49.6	61.4	38.8	from 7 to 18
38.147.21	With lock	Black	49.6	61.4	38.8	from 7 to 18



### Lock for small hatches/flush pulls

#### AISI 316

Snap lock with spring handle. Mirror-polished AISI 316 stainless steel.

Code	Lock	Accepts thicknesses mm	External Ø mm	Recess Ø mm	Depth mm
38.152.70	no	7 - 10	44	38	25.3
38.152.71	Yes	7 - 19	44	38	25.3



20.366.98 Spare key for 38.152.71.



### Flush pull latches small

#### AISI 316

Made of **mirror-polished AISI 316 stainless steel**. Equipped with square stop.

Code	Lock	Accepts thicknesses mm	External Ø mm	Recess Ø mm
38.147.05	no	5 - 12	62	48
38.147.06	Yes	5 - 12	62	48



38.147.06



38.147.05



38.147.06



38.147.05



38.147.06



Key for 38.147.06

### Flush pull latch with spring handle and snap lock

Mirror-polished AISI316 stainless steel.

Code	Lock	Accepts thicknesses mm	External Ø mm	Recess Ø mm	Version
38.152.05	no	5-12	62	50	Standard
38.152.06	Yes	5-12	62	50	Standard
38.152.08	Yes	5-12	62	50	Opening from inside and outside



20.366.98 Spare key for 38.152.06/08



20.366.98



38.152.08



38.152.05