

OSCULATI

▲ 38.161.01

▲ 38.161.02




▲ 38.161.61

▲ 38.161.62



▲ Spacer included

**Eclipse LIFT & TURN flush latch (with compression closure) - SMALL****COMPRESSION SYSTEM****EXTRA LARGE HANDLE**


Featuring a very comfortable grip, it offers all the best characteristics in a single flush deck design model.

- 316 mirror-polished stainless steel;
- flush aesthetics;
- large ergonomic handle;
- Handle can be lowered every 90°.
- Foldable handle every 90°;
- visual indicator open/closed;
- ergonomic nut for easy calibration and allowing for emergency exit;
- straight cam suitable for sliding door closure;
- cam with two possible positions;
- plastic spacer with invitations for custom cutting.


Polished SS version	Black SS version	Lock	External Ø mm	Bore Ø mm	Bulkhead thickness mm	Stop stroke mm
38.161.01	38.161.61	no	60	50	3-26	22-94
38.161.02	38.161.62	Yes	60	50	3-26	22-94



▲ Key for 38.161.02



▲ Universal straight cam included



▲ Angled cam included

**OSCULATI**

▲ 38.161.31

▲ 38.161.32



▲ 38.161.71/72




▲ Spacer included

Eclipse LIFT & TURN flush latch (with compression closure) - MEDIUM**COMPRESSION SYSTEM****EXTRA LARGE HANDLE**


Featuring a very comfortable grip, it offers all the best characteristics in a single flush deck design model.

- 316 mirror-polished stainless steel;
- flush aesthetics;
- large ergonomic handle;
- Handle can be lowered every 90°.
- Foldable handle every 90°;
- visual indicator open/closed;
- ergonomic nut for easy calibration and allowing for emergency exit;
- Straight cam suitable for sliding doors and having two different positions.
- plastic spacer with invitations for custom cutting.


Polished SS version	Black SS version	Lock	External Ø mm	Bore Ø mm	Bulkhead thickness mm	Stop stroke mm	Kit	No. of latches per kit (same key)
38.161.31	38.161.71	no	75	60	5-36	30-101	no	-
38.161.32	38.161.72	Yes	75	60	5-36	30-101	no	-
38.161.42	-	Yes	75	60	5-36	30-101	Yes	2
38.161.43	-	Yes	75	60	5-36	30-101	Yes	3
38.161.44	-	Yes	75	60	5-36	30-101	Yes	4
38.161.45	-	Yes	75	60	5-36	30-101	Yes	5



▲ Key for 38.161.32; 38.161.4x



▲ Universal straight cam included



▲ Angled cam included

