



Triangle for sail ties

Code	D mm	L mm	ORDER BY BOX
39.599.99	4	20	10
39.600.00	5	30	10
39.600.01	5	45	10
39.600.02	6	50	-
39.600.03	8	50	-



Triangle with bar for sail ties

Code	D mm	L mm	H mm	L1 mm	ORDER BY BOX
39.601.01	5	45	5.5	40	5
39.601.02	6	50	7	45	5
39.601.03	8	50	8	45	5



Semi-circle with bar for sail ties

Code	D mm	A mm	B mm	H1 mm
39.602.01	5	45	10	25
39.602.02	6	50	10	28
39.602.03	8	50	10	28
39.602.04	10	60	12	32

ROPEYE textile loops



▲ 39.811.01




▲ 39.810.02



▲ 39.810.01




▲ 39.811.02



ROPEYE XXS/XS stick-on textile loop

Ropeye has two different types of XXS loops: carbon & glass fibre. The loops are used as stick-on's on a sanded surface to glue the loops to. For elastic gluing: SIKAFLEX 291i 65.289.XX.


Code	Ropeye Code	Material	Top (A) mm	Ring (B) mm	Ø Base (C) mm	Width (D) mm	Weight g	Breaking load kg
39.810.01	ROXXS-C	Carbon fiber	3	20	30	3	3.0	75
39.810.02	ROXXS-GF	Fibreglass	3	20	30	3	3.0	75
39.811.01	ROXS-C	Carbon fiber	3	30	40	3	5.9	150
39.811.02	ROXS-GF	Fibreglass	3	30	40	3	5.9	150



ROPEYE TDP stick-on bushing for lines

Ropeye Through Deck Pushing is designed to protect the deck in the making of any thru-deck application for lines, halyards and sheets.


Code	Ropeye Code	Material	Ø head (A) mm	Internal diameter (B) mm	External diameter (C) mm	Length (D) mm	Weight g
39.817.01	ROTDP12	Anodised aluminum	28	8	12	30	8.2
39.817.02	ROTDP14	Anodised aluminum	30	10	14	30	10
39.817.03	ROTDP16	Anodised aluminum	32	12	16	30	11.5
39.817.04	ROTDP18	Anodised aluminum	34	14	18	30	12.3



ROPEYE SLR low-friction rings

Ropeye Self-Locking Rings are low-friction rings for indoor and outdoor applications. Made of anodised aluminium, they are specially designed to let lines, halyards and sheets slide inside the ring channel.

Code	Ropeye Code	Material	Exterior (A) mm	Interior (B) mm	Width (C) mm	Ring (D) mm	Weight g	Breaking load kg
39.819.01	ROSLR7-10	Aluminium	7	10	11	24	5	800
39.819.02	ROSLR10-14	Aluminium	10	14	15	34	13	1600
39.819.03	ROSLR14-20	Aluminium	14	20	20	46	30	3200
39.819.04	ROSLR20-28	Aluminium	20	28	31	70	120	6400
39.819.05	ROSLR28-38	Aluminium	28	38	44	99	290	10000



ROPEYE Eyestrapp Bridge

Ropeye Eyestrapp is a inside fastening point easy to install and very compact in size. For elastic gluing: SIKAFLEX 291i 65.289.XX.

Code	Ropeye Code	Material	Radius mm	Length mm	Width mm	Weight g	Breaking load kg
39.822.00	ROSOE	Carbon	9	50	14	2	35