

AISI316 stainless steel cleats

Hollow Cleat

AISI 316

Sturdy and practical, mirror-polished finish.

Code	Length mm	Centre distance mm		Breaking load kg	Subbase OPTIONAL
		Length	trans.		
40.132.12	125	54.2	24.7	2268	-
40.132.15	150	57.4	27.2	1103	40.132.45
40.132.20	200	71.2	33.3	4538	40.132.46
40.132.25	250	93.2	44.6	2900	40.132.47
40.132.30	300	100	49.2	4538	-

OSCULATI



Base

Made of **white plastic**, to be fitted as **washer** under cleats 40.132.15/20/25. It prevents oxide stains and gives the cleat a better finish.

Code	For bollards
40.132.45	40.132.15
40.132.46	40.132.20
40.132.47	40.132.25



Hollow cleat with oval section

AISI 316

Code	Length mm	Centre distance mm		Breaking load kg
		Length	trans.	
40.104.12	120	43.2	31.7	1660
40.104.15	150	55.3	38.9	1990
40.104.20	200	74.9	41	2990
40.104.25	250	93.2	47.5	3022

OSCULATI



HEAVY DUTY Hollow Cleat

AISI 316

Oversized version of series 40.132.15/30. Higher breaking load, sturdier look.

Code	Length mm	Centre distance mm		Breaking load kg
		Length	trans.	
40.134.20	200	84.5	45.2	2800
40.134.25	254	95.4	46.9	3200
40.134.30	305	121.7	63.3	3200
40.134.38	380	123.7	65.1	7200



HEAVY DUTY Hollow Cleat

AISI 316

Stud mounting, made of **mirror-polished AISI316 stainless steel**.

Code	Length mm	Centre distance mm	Breaking load kg
40.135.25	250	95.3	3200
40.135.30	300	122.4	3200



Italian Style cleat

AISI 316

Made of **AISI316 stainless steel**, tapered and aerodynamic design, special high-quality finish, 2-stud mounting.

Code	Length mm	Height mm	Centre distance mm	Stud Ø mm	Breaking load kg
40.174.18	180	32	59.6	8	3496
40.174.24	240	43	79.5	12	8127
40.174.30	300	70	103.3	16	5765
40.174.37	370	73	119.5	16	7613

OSCULATI

