

OSCULATI**Tapered base****AISI 316**

Made of precision-cast mirror-polished AISI316 stainless steel. 1 x 8-mm mounting stud.

Code	Version	Base measurement mm	Height mm	Slope	For pipe Ø mm	Studs and nuts optional	Studs mm
41.210.25	sloped	53x46	70	60°	25	40.142.08	8
41.110.30	sloped	66x51	80	60°	30	40.142.08	8
41.212.25	straight	Ø 44	70	90°	25	40.142.08	8
41.112.30	straight	Ø 51	80	90°	30	40.142.08	8

OSCULATI**Tapered base for pulpits****AISI 316**

Made of mirror-polished AISI316 stainless steel, 1 x 8-mm mounting stud.

Code	Slope	Base mm	Height mm	For pipe Ø mm	Optional studs and bolts	Studs mm
41.309.25	45°	62x45	75	25	40.142.08	8
41.310.25	60°	45	70	25	40.142.08	8
41.312.25	90°	45	57	25	40.142.08	8
41.409.30	45°	65x48	75	30	40.142.08	8
41.409.31*	45°	84x48	70	30	40.142.08	8
41.410.30	60°	48	70	30	40.142.08	8
41.412.30	90°	48	62	30	40.142.08	8

* Aerodynamic version

**White polyethylene underplate**

Code	Underplate	External Ø mm	Inside Ø mm	For bases	ORDER BY BOX
41.412.38	Round	50.5	46.5	41.412.30	10

**Pulpit joint****AISI 316**

Code	Version	Slope	For pipe Ø mm
41.118.22	bow or stern angle	110°	22
41.120.22	bow or stern angle	140°	22
41.119.22	bow or stern angle	90°	22
41.119.25	bow or stern angle	90°	25
41.121.22	three-way angle	90°	22
41.121.25	three-way angle	90°	25

**Rectangular fitting for pulpits**

Code	Version	Slope	Base mm	For pipe Ø mm
41.113.00	Rectangular	30°	75x42	22
41.165.00	Rectangular	45°	75x42	22

**Round fitting for pulpits**

Code	Version	Slope	For pipe Ø mm
41.112.00	Round	30°	22
41.127.00	Round	45°	22
41.112.01	Round	30°	25
41.127.01	Round	45°	25

**T joint for pulpits**

Code	Version	Slope	For pipe Ø mm
41.114.22	sloped	60°	22
41.114.25	sloped	60°	25
41.114.30	sloped	60°	30
41.115.22	straight	90°	22
41.115.25	straight	90°	25
41.115.30	straight	90°	30