

Kit of wireless independent LED lights

Power supply through built-in rechargeable batteries. Magnetic mounting with an operating range of 30 m. IP65 protection rating

Code	Type	Function	$\longleftrightarrow$ mm
02.023.24	Magnetic mounting	Position, Stop, Dynamic turn (inner-to-outer flashing), Plate, Triangles	110x110x37



Extension cable for boat trailer

For electronic signal transfer from the towing vehicle to the boat trailer. European connection. Waterproof and sturdy.

Code	V	Version	Length m
02.024.01	12	7-pole socket + 7-pole plug	5
02.024.02	12	7-pole socket + 7-pole plug	7
02.024.03	12	7-pole socket + 7-pole plug	10
02.024.05	12	2 x 7-pole plugs	8
02.024.06	12	2 x 7-pole plugs	7
02.024.07	12	2 x 7-pole plugs	10
02.024.08	12	2 x 13-pole plugs	5
02.024.09	12	2 x 13-pole plugs	7
02.024.10	12	2 x 13-pole plugs	10



02.024.08/09/10



02.024.01/02/03



02.024.05/06/07

Reflectors

Round or triangular. High visibility.

Code	Model	Version	$\longleftrightarrow$ mm
02.023.30	Orange retroreflector	Central hole	60
02.023.31	White reflector	Central hole	60
02.023.32	Adhesive orange reflector	Sticker	60
02.023.33	Adhesive white reflector	Sticker	60
02.023.36	Triangular reflector	Screws	70 (bore centre distance)



02.023.30



02.023.31



02.023.32



02.023.33



02.023.36

Type-approved speed disc

Self-adhesive fastening. 200-mm diameter.

Code	Description	Ø mm
02.023.40	Speed 70	200
02.023.41	Speed 80	200



02.023.40



02.023.41

Speed disc support

Made of flexible plastic, universal model.

Code	$\longleftrightarrow$ mm
02.023.50	300x200

