Polybridge II + EVA folding gangplank made of carbon

FPT (technical polyurethane) construction. Anodized aluminium hinges.

Wheels with stainless steel case to lift the gangplank. Double pivoting lock.

It can be mounted with a single pin to let the gangplank swing, or with two pins for mere tilting (both pins included).

The walking surface can be fitted with a white anti-slip cover, or covered in brown or grey EVA.

Code	Length m	Width	Length when folded m	Thickness when folded cm	Safety capacity kg	ķg.	Version
42.663.00	2.2	34	1.1	14	140	8	nonslip
42.663.10	2.2	34	1.1	14	140	8	w/brown EVA
42.663.20	2.2	34	1.1	14	140	8	w/grey EVA
42.663.61	2.6	34	1.3	14	140	10	nonslip













CARBONBRIDGE folding carbon gangway

High-Tech monocoque body made of carbon fibres previously impregnated with epoxy resins. High-resistance aluminium hinges, machined from solid and thick anodized in black colour. Aluminium pivoting pin. Antiskid walking surface.

Code	Length m	Width	Safety capacity kg	ķ.	OPTIONAL fastening bushing	Optional padded bag for transport/storage
42.665.00	2.2	35	150	6.5	42.659.10; 42.659.25; 42.660.25; 42.644.00	42.665.01





Replacement bushing for gangways



Made of nylon.

Code	Flange Ø mm	Bore Ø mm	
42.659.10	80	25	

Bushing for gangway swivel AISI 316



Made of AISI 316 stainless steel, fitted with lower water drain and cap.

Code	Flange Ø mm	Bore Ø mm	
42.659.25	80	25	

Adjustable bushing (+-30°)

AISI 316

Suitable for providing **wall supports** to the gangways; made of **mirror polished AISI 316 stainless steel**.

Code	Fixing base mm	Accepts gangway pins	Stud
42.660.25	100x80	25 mm	INCLUDED

