

TECNOSEAL

Spare anodes for Side-Power (Sleipner) bow/stern propellers

| Zinc | Aluminium | Orig. Ref. | Type propeller/engines |
|-----------|-----------|-------------|--|
| 43.070.20 | 43.070.21 | 61180 | SP-SE30/40 |
| 43.070.22 | 43.070.23 | 71190/51180 | SP55S/75T/95T, SE60/185S, SE80/185T/SE100 |
| 43.070.24 | - | 101180 | SP125T/285STC/SE120-150/SP220-300HYD/SH160 |
| - | 43.070.25 | 140629 | SR80/100/130/170/210/240 |
| 43.070.27 | 43.070.28 | 501180 | - |
| 43.070.29 | 43.070.30 | 31180 | - |
| 43.070.31 | 43.070.32 | 201180 | - |
| 43.070.33 | 43.070.34 | 02481 | - |











43.070.22/23













43.070.29/30




▲ 43.070.29/30











4 43.070.31/32

TECNOSEAL

Monitoring systems



ATOM TECNOSEAL Cathodic protection monitoring system

NMEA PROTOCOL

 $Electrochemical potential monitoring \ system \ used to continuously measure \ the \ cathodic \ protection \ conditions \ of \ submerged \ and \ semi-submerged \ metal \ appendages.$

To be installed in control panels having IP64 protection rating on the front, on hulls of any material. From a minimum of 1 to a maximum of 6 measurement points applicable.

It is available with two different probes complete with thru-hull fittings (3/4" in bronze) for monitoring:

- Pure zinc probe: more economical version suitable for medium boats. The zinc will need to be


- Pure zinc probe: more economical version suitable for medium boats. The zinc will need to be replaced every 2/3 years.
- Silver and silver chloride probe: premium version with several years of durability.
- Technical features of the screen:
- -4.3" TFT LCD screen, high brightness
- Resolution 480x272 pixels
- Spark plugs 700
- Resistive touch screen
- Power supply 12/24 V <500mA
- Dimensions 118x78x32 mm
- Drilling template 107x67 mm
- Operating temperature -20 +70 $^{\circ}\text{C}$
- Front material and casing: ABS
- Weight 200g

Order 43.850.00 + a chosen probe.



| Code | ode Transducer (including 3/4" bronze thru-hul | | | |
|-----------|--|----------------------------|--|--|
| | Zinc | Silver and silver chloride | | |
| 43.850.00 | 43.850.10 | 43.850.20 | | |







12 / 24 VDC IN



43.850.11 Only replacement zinc probe.

43.850.21 Only silver probe and replacement silver chloride.