


ULTRAFLEX steering systems - Rotary steering systems

ULTRAFLEX



Rotary steering System T 67

Suitable for outboard engines up to 55 HP, can also be used with Morse C230/231, Teleflex, Compact, TX805.

Only complete clutch box and hub cover 90° black
45.067.00


Only cable M 58
45.067.XX *



45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19
Terminals and brackets for any kind of steering wheel from this catalogue (OPTION).



Pls check the detailed table here below to choose the right product depending on the length needed.



Cable M58

For control box (model 45.067.00)

Code	length	Code	length	Code	length
45.067.07	7'	45.067.12	12'	45.067.17	17'
45.067.08	8'	45.067.13	13'	45.067.18	18'
45.067.09	9'	45.067.14	14'	45.067.20	20'
45.067.10	10'	45.067.15	15'	45.067.22	22'
45.067.11	11'	45.067.16	16'		

Rotary steering system T 71

For outboard engines, stern drive engines up to 9/10 meters and speed up to 50 MPH, 4 steering cycle, curve radius minimum cable 200 mm, stroke 228 mm.


Control mech only	M66 cable only	Cover		
		90° color black	90° chromed color	20° black color
45.055.00	45.185.xx*	45.055.02	45.055.05	45.055.03



45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19 Engine
side terminals and brackets for any kind of steering wheel from this catalogue (OPTION).



Pls refer to the detailed table at the end of the rotating system range to choose a cable of the right length.



▲ Planetary gear design

Rotary steering system T 85

For outboard, inboard and SX-drive engines up to 9/10 meters and maximum speed of 50 MPH, steering cycle 3, minimum curve radius 200 mm, stroke 228 mm.


Control mech and cover 90°	Cable M 66
45.185.00	45.185.xx *



45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19
Terminals and brackets for any kind of steering wheel from this catalogue (OPTION).



Pls refer to the detailed table at the end of the rotating system range to choose a cable of the right length.



Rotary steering system T 72

Designed for heavy power, hulls up to 10.50 meters and speed of over 50 MPH. Same features as model T71, but it works with two cables M66.


"T 72" control box only	M66 cable only	Cover		
		90° color black	90° chromed color	20° black color
45.072.00	45.185.xx*	45.055.02	45.055.02	45.055.03



45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.597.17; 45.595.18; 45.595.19 Optional
terminals and brackets to be chosen 45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19. It could be used with any kind of steering wheel from this catalogue (OPTION).



Pls refer to the detailed table at the end of the rotating system range to choose a cable of the right length.



▲ Planetary gear design