

Non-reversible rotary steering system T 73 RFC

Designed for hulls up to 9/10 meters and speed up to 50 MPH. This system allows you to leave the steering wheel without having the propeller cause vibration to the hull.

"T 73" control box only	M66 cable only	Cover		
		90° color black	90° chromed color	20° black color
45.073.00	45.185.xx*	45.055.05	45.05.05	45.055.03



45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19
side terminals and brackets for any kind of steering wheel from this catalogue (OPTION).


Engine



Pls refer to the detailed table at the end of the rotating system range to choose a cable of the right length.



▲ Planetary gear design



Rotary steering system with adjustable wheel orientation

Control box	Model	Version	M66 cable only	Hub at 90° with mechanism for tilt up to 48°
45.081.00	T 81 FC	Single for boats up to 9/10 meters	45.185.xx *	45.038.00
45.083.00	T 83	Single non reversible for boats up to 9/10 m	45.185.xx *	45.038.00



45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19
Terminals and brackets for any kind of steering wheel from this catalogue (OPTION).



Pls refer to the detailed table at the end of the rotating system range to choose a cable of the right length.



▲ Planetary gear design





▲ 45.038.00



T91/T93ZT rotary steering systems

Features: high efficiency; patented M90 Mach quick-coupling cable. **Attention:** M90 Mach cable is also suitable for use with steering wheels using M66 cables but these latter are not fit for T91/T93ZT steering systems; Engine side stainless steel cable with watertight seal; Central shaft for easy installation; 4.2 steering wheel turns, 228-mm cable stroke, 408-mm Ø steering wheel, 200-mm minimum steering cable bend radius. Recommended for boats not faster than 50 MPH. Not to be used on boats equipped with engines that exceed the maximum HP rating of the boat. T93ZT non-reversible version. It isn't necessary to remove the steering wheel since the propeller rotation will not make the boat veer.

Code	Description	M90 Mach cable	Cover			Anti-theft device with chromed hub cover
			90° color black	90° chromed color	20° black color	
45.060.00	Single steering system	45.186.xx	45.055.02	45.055.05	45.055.03	45.055.06
45.061.00	Non reversible steering system	45.186.xx	45.055.02	45.055.05	45.055.03	45.055.06



▲ 45.060.00; 45.061.00



▲ 45.055.06



▲ Planetary gear design




▲ 45.060.00



▲ 45.061.00



▲ 45.061.00



▲ 45.055.02/03




▲ 45.055.02/03

T101/T103ZT rotary steering systems with adjustable wheel orientation

M90 Mach patented steering cable. Same technical specification as 45.060.00 and 45.061.00. For max 50 MPH speed. Do not install on boats with more powerful engines.

Code	Description	M90 Mach cable	90° hub for inclination of steering system up to 48°
45.062.00	Single steering system	45.186.xx	45.038.00
45.063.00	Non reversible steering system	45.186.xx	45.038.00

▲ 45.062.00/45.063.00-45.038.00



▲ Planetary gear design



▲ 45.062.00



▲ 45.062.00+45.038.00



▲ 45.063.00



▲ 45.038.00