



Pair of high-pressure hoses Silver Steer

Kit including a pair of high-resistance hoses reinforced with pre-crimped fittings and anti-crush reinforcing sleeves.

Code	Type	Length m
45.277.55	OB-SVS 55	5.5
45.277.60	OB-SVS 60	6
45.277.65	OB-SVS 65	6.5
45.277.70	OB-SVS 70	7
45.277.80	OB-SVS 80	8



Double cylinder/double engine coupling kit for UC-130-SVS cylinders

Code	Engine centre distance mm	Hose length mm
45.278.01	660	381
45.278.02	686	407
45.278.03	711	432
45.278.04	724	445
45.278.05	737	457
45.278.06	762	483
45.278.07	777	496



Connecting rod

Code 45.560.00

Stainless steel with ball terminal joints, used to connect the main engine with an auxiliary one; the auxiliary steering can be handled with the boat steering system. Adjustable length **from 45 to 60cm**, easy to remove thanks to its spring ball fitting.

Connecting rod

For outboard engines, made of stainless steel.

Code	Type	Steering systems	Engine centre distance mm
45.156.08	A92, easily adjustable, for small spaces	hydraulic/mechanical	550/700
45.156.09	A92, easily adjustable, for small spaces	hydraulic/mechanical	700/950
45.156.10	A88	hydraulic/mechanical	650/950

SUZUKI DF100/115/140 coupling rod

Code 45.156.33

For double engine/double cylinder. 660/950-mm engine centre distance.

Coupling rod for outboard engine with hydraulic steering

Double/triple engine, with brackets, UC128/UC130 cylinders. All parts made of stainless steel.

Code	Model	Cylinder type	Independent tilting	Engine centre distance mm
45.156.19	A96-29	Single	Yes	660/736
45.156.20	A96-34-5	Single	Yes	736/873
45.156.15	A95-32	Double	Yes	660/813
45.156.16	A95-375	Double	Yes	813/952
45.156.17	A97-30	Double	Yes	660/762
45.156.18	A97-35.5	Double	Yes	762/901
45.156.25	A96-B29	Single	Yes	660-736
45.156.26	A96-B34-5	Single	Yes	736-873
45.156.27	A95-B32	Double	Yes	660-813
45.156.28	A95-B37-5	Double	Yes	813-952
45.156.29	A97-B30	Double	Yes	660-762
45.156.30	A97-B35-5	Double	Yes	762-901

