

## Bimini top with carbon tubes



Bimini top modular system. High finish with mirror-polished swivel-lock bushings.



### Carbon pole for Bimini top

The pole rotates by 90° inside the bushing and locks. The poles are fitted with tightening bushings. Clamcleat for easy adjustment and tensioning of the Bimini top already mounted on the pole. Compatible with recess-fit bushings 46.815.xx and 46.280.xx. Fastening rope: eye spliced Dyneema rope. It can be used for direct installation on the Bimini top by means of a 10-mm Ø pawl or a snap hook. Rope not included with the pole.

Code	Ø mm	Height cm	Optional wall mounting clip
46.816.02	38	130	34.358.38
46.816.04	38	150	34.358.38
46.816.06	38	170	34.358.38
46.816.07	38	185	34.358.38
46.816.08	38	200	34.358.38
46.816.10	38	230	34.358.38
46.821.02	50	170	34.358.50
46.821.04	50	200	34.358.50
46.821.06	50	230	34.358.50

46.817.00 MARLOW spliced line, length 130 cm with 50 cm adjustment



### Removable carbon pole for Bimini top

#### 2 PCS MOUNT POLE

The pole is made up of two section and is fitted with anticorodal aluminium bushings for fast mounting. Tightening bushings and a fastening line are also supplied. The pole rotates by 90° inside the busing and locks. Clamcleat for easy adjustment and tensioning of the Bimini top already mounted on the pole. Compatible with recess-mount bushings 46.815.00/01, the bulkhead mount bushing kit 46.815.10 and the bulkhead mount stowage system 34.358.38. Fastening line made of spliced Dyneema with eye. It can be used for direct fastening to the Bimini top with a 10-mm Ø ball or a shackle.

Code	Ø mm	Height cm	No of sections
46.818.09	38	90/181	2
46.818.11	38	110/231	2

46.817.00 MARLOW spliced line, length 130 cm with 50 cm adjustment

34.358.38 Bulkhead stowage system

