



▲ 1



▲ 1



▲ 2



▲ 1



▲ 3



▲ 4

INDOOR sea cover

Polyethylene sheet to protect boats in marinas. Supplied in 50-m rolls with continuous elastics on the outer sides. It comes in rolls of 50 m, with two continuous elastics inserted on the outer edges.

Installation instructions

- 1) Unroll the cover from stern to bow, keeping central to the vessel, leaving an excess of about 50 cm on each side.
- 2) Apply two ties spaced about 30 cm apart and cut the covering used from the rest of the coil.
- 3) Extract the elastics and tie them.
- 4) Open the cover on the vessel.
- 5) Pull the elastic from one end and tie it to keep it under tension.
- 6) Use the specific pre-cuts with reinforcements if necessary to connect the transverse perimeter elastic.

Code	Cover width m	Roll length m
46.174.00	4	50
46.174.01	6	50
46.174.02	8	50
46.174.03	10	50
46.174.04	15	50



▲ 5



▲ 6

Marine heat-shrink covering

White polyethylene heat-shrink film. Special additive for UV-ray resistance. Ideal covering to protect whatever boat from dirt, minor impacts, high temperature, etc. during laying up/transport. Easy application by spreading the product from bow to stern and heating it up with the dedicated heat guns.

Product sold in rolls (price depends on weight).



Code	Film width m	Roll length m	Roll height m	Thick-ness mm	Appro-ximate weigh kg	Bending	UV ray resistance
46.176.07 New	6	50	1.5/1.6	0.2	62	bellows-bending	12 months guaranteed
46.176.08	8	50	1	0.2	77.7	multiple bending	12 months guaranteed
46.176.10	10	50	1.25	0.2	97.1	multiple bending	12 months guaranteed
46.176.12	12	50	1.5	0.2	116.5	multiple bending	12 months guaranteed
46.176.14	14	50	1.75	0.2	135.9	multiple bending	12 months guaranteed
46.176.17 New	16	50	2	0.2	161	multiple bending	12 months guaranteed



▲ 46.176.08/10/12/14/17



▲ 46.176.07