

Air vents for heat-shrinking covering

Good protection against the ingress of unwanted external agents to prevent condensate, mould and bad odours

Code	Description
46.188.01	Pierciąg triangular vent
46.188.02	Adhesive round vent




Rafale Black Edition + propane gas shrinkforming gun

Propane gas shrinkforming gun for polyethylene. Weighing 1.17 kg, and combining ergonomics and comfortable noise levels (88dB at 1-m distance - 85dB), Rafale Black Edition has been designed to limit user's fatigue as much as possible, even after several working hours. Air consumption: 48 to 72.2 m³/h; flow: 3.2 to 4.8 kg/h. 1.3-mm diameter injector, 360° swivelling head for use in any position. Aluminium nozzle surrounded by a double protection, which means that it always stays warm regardless of the duration and intensity of use. Power can be set from 44 to 66 kW/h. Delivered in a case containing: pressure regulator adjustable from 1.5 to 3.5 bar, 8-m rubber hose complying with NF EN 559, 1 instruction manual, 1 pair of gloves, 1 heat deflector. CE mark No 4450.

Code	Description
46.177.00	Propane gas shrinkforming gun (faucet not included)
46.177.10	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Algeria, Belgium, Spain, France, Hungary, Luxembourg, Morocco, Holland, Poland, Portugal, Czech Republic, Switzerland, Tunisia.
46.177.12	Pressure regulator and pressure gauge for shrinkforming gun with fitting for UK, Canada, Ireland.
46.177.13	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Italy and Greece.
46.177.15	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Turkey.
46.177.16	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Russia.

To use the gun, also order the suitable fitting (to be chosen depending on the country of use).



Gas cylinder trolley

The cylinder trolley is easy to assemble, lightweight, foldable, and manageable. Comes with straps that serve to secure the cylinder during transport and a special support for the heat gun (code 46.177.00).

Code	Max load kg	Wheel Ø mm	mm		kg
			open (LxWxH)	closed (LxWxH)	
46.177.30	13	145	106x45x40	60x40x26	7.5



Heat-shrinking polyethylene adhesive tape

To join, seal and repair heat-shrinking film. Also used when installing fixtures such as doors, openings, vents, etc. Resistant to abrasion, UV rays, weather and chemical agents.

Code	Width mm	Length mm
46.186.00	50	33
46.186.01	96	55



Polyethylene doors and openings.

To enable access to the structure.

Code	Outside mm	Closing
46.187.01	1750x750	Zip

