

Straps ideal for mooring to the ground

Bands particularly resistant to abrasion, ideal for mooring to rocks or rough rings that wear out normal mooring lines.

Particularly suitable for working in combination with the ropes 06.479.XX.

Code	Colour	Length m	Working load kg	Tape height mm
06.480.02	Purple	2.5	1000	65
06.480.04	green	3.5	2000	65



Megayacht double mooring braid

MADE IN ITALY

Made of high-tenacity polyester.

Double braid processing with opposing twisted yarns.

This process guarantees:

- softness;
- toughness;
- resistance to abrasion;
- anti-twisting effect;
- Ease of splicing.

Sold by the spool.

Code	Colour	Ø mm	Strands	Breaking load kg	Spool m
06.470.24	black	24	24	13000	100
06.470.28	black	28	24	18000	100
06.470.32	black	32	24	22400	100
06.470.36	black	36	36	26000	100
06.470.40	black	40	36	30500	100



Anchor rope made of polyester braid with lead core for the first 10 metres

With thimble and spliced by hand.

It comes in an elegant nylon bag with blue string.

Code	Ø mm	Length m	Lead core length m	Lead weight kg	Total weight kg
06.446.10	10	30	10	3	5
06.446.12	12	30	10	4	7.5
06.446.13	12	50	20	8	10



Pieces of polyester braid

White colour with fleck, pre-packed, with splicing and nylon thimbles.

Code	Ø mm	Length m	Code	Ø mm	Length m
06.442.01	8	15	06.442.04	10	15
06.442.02	8	30	06.442.05	10	30
06.442.03	8	40	06.442.06	10	40



Polypropylene rope with 32 strands

Specially designed for the attachment of fenders.

Manufactured without a core and very easy to weight without any specific knowledge.

Sold by the spool.

white	Blu navy	black	grey	Nominal Ø mm	Flat braid mm	Spool m
06.444.10	06.444.20	06.444.80	06.444.70	10	3.3 x 18	50
06.444.11	06.444.21	06.444.81	06.444.71	14	4.5 x 20	50
06.444.12	06.444.22	06.444.82	06.444.72	18	5.6 x 25	50

OSCULATI

