

Gas bottle cock



Code 50.013.10
With overpressure safety device. M16x1.5 thread + shell.

30-Mb pressure regulator with monometer



Code 50.013.12
Shell thread (connection to 50.013.10) + 1/4 (connection to 50.013.25/26/27).

M5 fittings

8+8-mm femal fitting, DIN 8434-1.



▲ 50.013.41



▲ 50.013.40



▲ 50.013.44



▲ 50.013.43



▲ 50.013.42

Code	Type
50.013.40	bulkhead-pass
50.013.41	90° bulkhead
50.013.42	Tee
50.013.43	elbow 90°
50.013.44	Straight

Spare ogive for 8-mm copper tube fittings



Code 50.013.97
To be replaced any time the tube is changed.
5-pcs display blister.

Brass nut for 8-mm copper tube, M14 x 1.5F pitch.



Code 50.013.98
3-pcs display blister.

Shut-off valve with fixing plate



Code 50.013.14
DIN EN12514-2 - EN331. 8+8-mm female fitting
(connection to tubes 50.013.25 and copper pipe).




Gas leak detector

This device has to be installed near the gas bottle, downstream the pressure regulator. It detects possible gas leaks downstream the butane bottle.

Code	Model
50.013.16	Universal for RST8 copper pipes or rubber tubes

Pots and kitchen accessories

Toaster



Made of **stainless steel**. To be used on an onboard kitchen burner.

Code	base mm
50.819.00	136x113

Waste container fitted with snap-in locking

OSCULATI



Code 50.420.01
Uses standard waste bags, the automatic locking system prevents bad odours leakages.