

isotemp


50.198.58

ISOTEMP INDEL WEBASTO MARINE boiler - SPA series

AISI 316 stainless steel internal tank and corrugated coil. Grey propylene extrenal shell. 750 W 220 V **nickel-plated copper** electric resistance. Safety valve set at 6 bar. CFC-free polyurethane foam insulation. AISI 304 stainless steel fixing brackets. Thermostatic mixer 50.189.58 to be purchased separately.

Code	Type	Volume litres	LxØ mm	Max pressure bar	W*	kg
50.292.01	SPA15	15	450x310	6	750	7.5
50.292.02	SPA20	20	550x310	6	750	9
50.292.03	SPA25	25	650x310	6	750	10
50.292.04	SPA30	30	535x390	6	750	12
50.292.05	SPA40	40	640x390	6	750	14
50.292.06	SPA50	50	745x392	6	750	15
50.292.07	SPA60	60	850x392	6	750	17

* 1200 W resistance


isotemp


50.291.00/20



50.291.04





50.290.00

ISOTEMP INDEL WEBASTO MARINE boiler

Stainless steel internal tank, coil and external cover. The tank has a 5-year warranty against leaks. It works with a 750W 220V **nickel-plated copper** resistance or with a heat exchanger connected to the engine cooling system. The resistance is positioned on the lower part of the boiler to avoid heat stratification. Fitted with dual safety/service thermostat and 7-bar safety valve. Polyurethane foam insulation, horizontal or vertical installation.

Code	Volume litres	LxØ mm	Max pressure bar	Electric resistance W	kg
50.291.00	15	520x295	7	750	9
50.291.20	20	645x295	7	750	10.5
50.291.01	25	765x295	7	750	12
50.291.25	24	470x395	7	750	12.5
50.291.02	40	640x395	7	750	15.5
50.291.03	50	760x395	7	750	17
50.291.04	75	1050x395	7	750	24.5
50.290.00*	16	560x400x180	5	750	15.5

* Thermostatic mixer not included.



50.290.00

Thermostatic mixer for water heaters

Code 50.189.58

Designed to adjust the output temperature of hot water to avoid **high temperatures**, universal size fits all water heaters.

Water heater joint hot water outlet pipe

Code 50.289.56

Made with **stainless steel** metal braid, replaces PVC pipe that does not withstand high temperatures from the boiler water output, length 45 cm, standard size screw thread 1/2".