

**New****ISOTHERM VE200 PLUG&PLAY Cooling Unit****PLUG&PLAY**

VE200 PLUG&PLAY cooling unit is the ideal solution to turn unused spaces into refrigerated areas. Easy to install, no qualified technicians required. Pre-assembled, pre-charged with refrigerant gas.

Code	Max volume		V	Compressor	Temperature range	↔  mm	
	Fridge	Freezer				Evaporator	Compressor
50.931.95*	200	65	12/24*	BD35F	+0° +11°	360x257x258	280x160x175

\* AC/DC option through Isotherm power pack.

**isotherm****Accessories for refrigerators****INDEL WEBASTO MARINE ISOTHERM Smart Energy Control**

By means of a sophisticated micro-processor, this device drastically reduces the energy consumption of fridges and refrigerating units. It continuously adjusts the compressor RPM and, by means of a special sensor, it detects the refrigerator air temperature thus cooling food a bit more than necessary when the boat engine is on or when the boat is connected to the dock. During navigation, it exploits the food surplus frigories to reduce the compressor operation with an energy saving of about 50%. This device can match any fridge or refrigerating unit fitted with SECOP 101N0212 electronic unit. The kit includes: panel with micro-processor, adjustable potentiometer, air sensor.

Code	Input Voltage (AC)	↔  mm
50.932.20	12/24	225x155x80

**isotherm****Power Pack ISOTHERM 108W VAC 50/60HZ 24V for refrigerators**

Optimised for the absorption curves of our compressors, it allows refrigerators and Isotherm units to be universally powered, with DC 12/24V and AC 115/220V 50/60Hz voltage.

High output power up to 108W. Lightweight and compact in size. Suitable for various compressor models.

Compatible with all Isotherm refrigerators that are 12/24V and have a BD35 / BD50 / BDMICRO 1.4 compressor.

Code	V		Output power W	Output current A	↔  mm
	input (AC)	output (DC)			
50.820.02	100-240	26.5	> 108	> 4.5	131x35x255

**isotherm****ISOTHERM fridges****isotherm****DIVINO THE ONE electric glacette**

Recess-fit cooling device for bottles. It keeps the wine or champagne perfectly refrigerated. Touch the stainless steel crown to activate it. Interactive LED lighting with 27 colour options. IP65 on the outer side, IP22 on the inner side.

Code	Capacity	V	Power W	Bore Ø mm	Ring Ø mm	Depth mm	Inner light
50.835.20	1 bottle	12	60	152	169	301	27 colour options

**Isotherm refrigerator with hermetic Secop compressor, maintenance-free, 42 l - silver door**

Fitted with electronic control that turns off the fridge when the voltage goes under 10.4 volts and that starts up again when voltage goes up to 11.7 volt (adjustable values respectively up to 9,6 and 10,9 volt).

Rotation speed at 2000-2500-3000 RPM adjusted according to the volume to be cooled.

Forced ventilation. Compressor can be remote controlled.

Current draw: 275 W/24h.



Code	Model	Capacity l	V	Eutectic plate cool accumulation	Compartment	↔  mm			OPTIONAL finishing frame		kg
						Width	depth	Height	Black	SS	
50.830.04	CR42/V	42	12/24	no	Single	380	452/310	520	50.934.01	50.934.02	13.5
50.833.01	CR42EN	42	12/24	Yes	Single	380	475/310	530	50.934.01	50.934.02	17