

## ISOTHERM refrigerator with maintenance-free Secop hermetic compressor - double compartment

Fitted with electronic control that turns off the fridge when the voltage goes under 10.4 volts and that starts up again when voltage goes up to 11.7 volt (adjustable values respectively up to 9,6 and 10,9 volt).

2000-2500-3000 RPM rotation speed adjusted according to the cooling volume. Forced cooling.

Code	Model	Finish	Capacity I	v	Current draw (W/24h) A	l←→l <sub>mm</sub>			<u> </u>
ooue	Wodel	i iiii3ii	Capacity	,	Current araw (W/2411) A	Width	depth	Height	kg
50.838.05	CR225	Silver	225	12/24	650	566	491	1440	44
50.838.06	CR280	Silver	280	12/24	-	566	491	1700	50







## Classic trim frame for built-in mounting

Code	Series	Version	Forl	Inside dimensions (fixing) mm	Outside dimensions (look) mm	Sides
50.934.01	Classic	Black	42/49	380	422	3
50.934.02	Classic	Satin-finish SS	42/49	380	422	3
50.934.03	Classic	Satin-finish SS	65	450	492	3
50.934.04	Classic	Black	85	Height 625	Width 35	2
50.934.06	Classic	Black	130	526	564	3





## ISOTHERM Cruise Elegance refrigerator

 $New \, range \, of \, products \, with \, front \, door \, and \, different \, technical \, characteristics \, in \, comparison \, with \, the \, in the interpretation of the comparison in the interpretation of the comparison of the comparis$  $standard\,line: door\,ventilation\,system\,built\,in\,the\,cover\,lid; easy fix\,system\,for\,installation\,from\,inside$ the cabinet; freezer compartment featuring a new design features such as steel door and high-power LED internal lighting. Fitted with safety closure.

Code	Model	Capacity I	v	Current draw (W/24h) A	l←→I <sub>mm</sub>			OPTIONAL silver finishing frame	
					L	Р	Н	3 sides	4th side
50.827.18	CR42E	42	12/24	265	380	452	525	50.934.10	50.934.21
50.827.20	CR49E	49	12/24	265	381	500	520	50.934.10	50.934.21
50.827.22	CR65E	65	12/24	275	448	530	527	50.934.11	-
50.827.24	CR85E	85	12/24	368	477	555	620	50.934.12	-
50.827.26	CR130E	130	12/24	418	528	555	746	50.934.13	-



Standard silver finishing for panel/door

**50.932.20**OPTIONAL Smart Energy Control for energy absorption up to 25%









## Elegance series trim frame for flush mounting

Code	Series	Version	Forl	Inside dimensions (fixing) mm	Outside dimensions (look) mm	Sides
50.934.10	Elegance	Silver	42/49	380	422	3
50.934.11	Elegance	Silver	65	450	493	3
50.934.12	Elegance	Silver	85	476	541	3
50.934.13	Elegance	Silver	130	525	592	3
50.934.21	Elegance	Silver	49	322	424	4° (lower part)