


ISOTHERM refrigerator with stainless steel panel - clean touch

Fitted with flange for recess fit: the door is flush with the flange. Snap lock door, quite 12/24V SECOP compressor, inside LED light. Ready to fit smart energy control 50.932.20. Clean touch film, stainless steel panel freezer, improved insulation door and ergonomic handle.

Code	Model	Capacity l	V	Consumption W/24h	mm			kg	OPTIONAL SS finishing frame on 4th side
					L	P	H		
50.827.30*	CR42 SS CT	42	12/24	285	400	500/385	525	17	50.934.27
50.827.31	CR49 SS CT	49	12/24	265	400	500	525	18	50.934.27
50.827.32	CR65 SS CT	65	12/24	275	470	520	528	20	50.934.28
50.827.33	CR85 SS CT	85	12/24	368	495	550	625	24	50.934.24
50.827.34	CR130 SS CT	130	12/24	418	545	555	750	29	50.934.31

Dimensions of the refrigerator do not include the mounting flange.

* Compressor can be remote operated up to 1.5 m. In this case depth is 385 mm.



▲ 50.827.30/31



▲ 50.827.32



▲ 50.827.33



▲ 50.827.34

ISOTHERM refrigerator with stainless steel front panel - double compartment

Complete with a flush-mount stainless steel flange, it allows installation of the door with a flush appearance. Closure by means of a flush snap lock. CR220 model: 130-l front door upper unit + 90-l front door lower freezer unit. CR260 model: 130-l front door hybrid upper unit + 130-l drawer unit (with 9.8-l freezer compartment).

Code	Model	Capacity l		V	Current draw A	mm			kg
		refrigerator	freezer			L	P	H	
50.827.05**	CR195 SS	130	65	12/24	2.3/6.2	545	580	1345	63
50.827.07**	CR200 SS*	150	50	12/24	2.3/6	735	620	880	53
50.827.16	CR220 SS	130	90	12/24	2/4	545	565	1538	69
50.827.15	CR260 SS	130+130	-	12/24	2/4	545	565	1538	74

* Complete with AC-DC 115/230 kit


** Refrigerator with freezer.



▲ 50.827.05



▲ 50.827.05



▲ 50.827.15



▲ 50.827.16



▲ 50.827.07