

### ISOTHERM Cruise 90 Classic and Cruise 90 Inox freezer

Extra-thick insulation for excellent cooling performance and low current draw.  
Fitted with built-in compressor.  
Current draw: 550 W/24h.

Code	Model	Description	Capacity l	V	WxDxH mm
50.839.00	CR90 Freezer classic	Door with safety lock and magnetic rubber seal	90	12/24	527x520x746
50.827.23	CR90-F-CT	SS front panel with touch finish. Fitted with recess fit SS fastening flange and door flush with the flange. Flush snap lock.	90	12/24	545x565x750



### ISOTHERM 130-I refrigerator with stainless steel front panel

Fitted with a flush-mount stainless steel flange, it allows installation of the door with a flush appearance. Flush snap lock.

Code	Model	Capacity l	V	Current draw A	WxDxH mm		
					L	P	H
50.827.14	CR130 DRINK SS	130	12/24	1.4/5.2	545	545	755



### ISOTHERM drawer refrigerator

Fitted with stainless steel rails and black or silver painted stainless steel door. Elegance line and user-friendly digital display.  
Silent and high-efficiency BD 12/24V 1.4F Secop compressor.  
Easy Fix system.

Code	Model	Capacity l	V	Current draw W / 24 hours	WxDxH mm	Colour	OPTIONAL frame for external mounting
50.826.09	DR16	16	12/24	160	250x380x540	Silver	50.934.26
50.826.14	DR30	30	12/24	270	260x440x700	Silver	50.826.24
50.826.15	DR30	30	12/24	270	260x440x700	Black	50.826.25
50.826.16	DR30	30	12/24	270	260x440x700	white	-



### Drawer series recess-fit finish frame

Code	Series	Version	For l	Inside dimensions (fixing) mm	Outside dimensions (look) mm	Sides
50.934.23	Drawer	Satin-finish SS	55	456	508	4° (lower part)
50.934.25	Drawer	Satin-finish SS	160	614	664	4° (lower part)
50.934.26	Drawer	Satin-finish SS	16	386	444	4 sides
50.934.27	Drawer	SS CT	49	384	438	4° (lower part)
50.934.28	Drawer	SS CT	65	452	508	4° (lower part)