

00.835.05

ISOTHERM top-loading cooling box by Indel Webasto

Small size and high-performing, access from top lid. Fitted with SECOP last-generation compressor.

Code	Model	Lid	Thermosts	Capacity I	V	←→ _{mm}	o kg
50.835.00	BI16	Opens with hinge	Digital	16	12/24	384x240x557	11.9
50.835.05	5.05 BI30 Opens with hinge		Digital	30	12/24	449x724x240	18
50.835.10*	BI36	Removable	Mechanical	35.5	12/24	438x556 + 125x240	15.3

130 mm space requirement for remote compressor.









Fridge/freezer Isotherm model BI29

Fully removable, fitted with roller slides. Single lid for access from the top. Stainless steel inner lining and plastic bottom. $+10^{\circ}$ /- 12° C temperature.

Code	Model	Capacity I	v	Energy consumption W/24h	←→ _{mm}	о к о
50.826.02	BI29	29	12/24	175	650x342x365	18





ISOTHERM - "Cruise 40 Cubic" 40-I cockpit refrigerator/freezer

Very versatile product that can be used as refrigerator and freezer. It can be installed for front or top opening. The SECOP compressor can be radio remote controlled uo to 1.3-m distance. White door that can be covered with a panel, coating to be varied according to the customer's needs.

			With	front door	With		
	Code	Power V	Current draw A	Adjustable temperature range	Consum- ption (W/24h)	Adjustable temperature range	o kg
	50 039 00	12/24	0 186 Kwh/24 h	+10°/-12°	186	+10°/-18°	17.6







 $Fitted with {\it plastic}\ bottom, internal removable baskets, Secop compressor with 12/24 volt universal voltage.$

	Туре	Capacity I	Version		Current	late week	14	
Code			refrigera- tor	freezer	draw W / 24 hours	Internal coating inox	←→ Housing mm HxPxL	
50.040.00	BI40	40	х	-	270	no	405x420x400+160*	
50.041.00*	BI41	41	x	Х	222	no	342x451+161x500	
50.042.00**	BI75	75	x	-	340	Yes	430x470+160*x650	
50.043.00**	BI92	95	х	х	360 Yes		485x455+160*x805	

Compressor can be remote controlled up to 0.90 m - reduces height by 161 mm
Furniture with bevelled lower part for better hull adhesion.







