

DOMETIC refrigerators

^> DOMETIC

DOMETIC refrigerator

 $Innovative \ design \ and \ high \ energetic \ efficiency for \ a \ 3-in-1 \ cooling \ solution: \ refrigerator \ only, freezer \ only, or both.$ The freezer compartment can be easily pulled out to make room for a larger refrigeration.

- Touch control panel with integrated LED light bar;
- Reversible door hinge;
- Full-width door handle neatly integrated for easy access;
- Smart closing mechanism to create a gap between the fridge and the door to airing out;
- Energy-efficient, light, compact compressor with 3 operating modes (Eco/Boost/Silent);
- Compressor can be remote-controlled in the 35-litre version to reduce depth to minimum;

▲ 50.915.xx

- Standard or flush-mount installation frame.

| Dark silver door | Stainless steel panel | Model | CapacityI | v | Average current draw W | $\left \longleftrightarrow\right _{mm(LxHxP)}$ | kg. |
|------------------|-----------------------|---------|-----------|-------|------------------------|--|-----|
| 50.914.01 | 50.915.01 | NRX0035 | 34 | 12/24 | 0.2296 | 380x355x525 | 16 |
| 50.914.03 | 50.915.03 | NRX0050 | 46 | 12/24 | 0.2222 | 380x510x525 | 17 |
| 50.914.05 | 50.915.05 | NRX0060 | 58 | 12/24 | 0.2335 | 448x537x525 | 17 |
| 50.914.07 | 50.915.07 | NRX0080 | 78 | 12/24 | 0.3036 | 475x537x625 | 20 |
| 50.914.09 | 50.915.09 | NRX0115 | 116 | 12/24 | 0.3671 | 525x568x745 | 25 |
| 50.914.11 | 50.915.11 | NRX0130 | 130 | 12/24 | 0.3729 | 525x568x812 | 26 |























${\bf Frame \, for \, DOMETIC \, refriger ators \, }$

| Code | Fridge model | Туре | |
|-----------|---------------------------|------------------------|--|
| 50.907.03 | NRX 35/50 dark silver | Flush-mounted/standard | |
| 50.907.05 | NRX 60 dark silver | Flush-mounted/standard | |
| 50.907.07 | NRX 80 dark silver | Flush-mounted/standard | |
| 50.907.09 | NRX 115 dark silver | Flush-mounted/standard | |
| 50.907.11 | NRX 130 dark silver | Flush-mounted/standard | |
| 50.908.03 | NRX 35/50 stainless steel | Flush-mounted/standard | |
| 50.908.05 | NRX 60 Stainless Steel | Flush-mounted/standard | |
| 50.908.07 | NRX 80 stainless steel | Flush-mounted/standard | |
| 50.908.09 | NRX 115 stainless steel | Flush-mounted/standard | |
| 50.908.11 | NRX 130 stainless steel | Flush-mounted/standard | |



CoolPower





 $CoolPower \, DPS-R \, 135 \, is \, a \, network \, adapter for connecting \, refrigerators \, with an \, electronic \, control \, unit for \, 12/24 \, V \, to \, the \, network \, 100-240 \, V. \, Output \, voltage \, 24V. \, Suitable for all \, DOMETIC \, refrigerators \, up \, to \, 135W.$

| Code | Power w/Ah | ←→ _{mm (LxHxP)} | | |
|-----------|------------|---------------------------|--|--|
| 50.820.10 | 135/1.53 | 110x32x100 | | |