



▲ 50.917.03/05



▲ 50.916.03/05

**New****DOMETIC drawer refrigerators**

Innovative design and high energetic efficiency for a 3-in-1 cooling solution: refrigerator only, freezer only, or both.

The freezer compartment can be easily pulled out to make room for a larger refrigeration.

- Touch control panel with integrated LED light bar;
- Reversible door hinge;
- Full-width door handle neatly integrated for easy access;
- Smart closing mechanism to create a gap between the fridge and the door to airing out;
- Energy-efficient, light, compact compressor with 3 operating modes (Eco/Boost/Silent);
- Compressor can be remote-controlled in the 35-litre version to reduce depth to minimum;
- Standard or flush-mount installation frame.

Dark silver door	Stainless steel panel	Model	Capacity l	V	Consumption W/24 h	↔ mm (LxHxP)	kg
50.916.03	50.917.03	NRX0050	46	12/24	222	380x510x525	17
50.916.05	50.917.05	NRX0060	58	12/24	234	448x537x525	17



▲ 50.918.01-07

**New****DOMETIC refrigerators, deep black**


Refrigerators with dark black panel. Equipped with 3 convenient shelves and a small compartment for bottles or cans. Freezer compartment can be ordered separately as an accessory.

- Touch control panel with integrated LED light bar;
- Reversible door hinge;
- Full-width door handle neatly integrated for easy access;
- Energy-efficient, light, compact compressor with 3 operating modes (Eco/Boost/Silent);
- Compressor can be remote-controlled in the 35-litre version to reduce depth to minimum;
- Standard or flush-mount installation frame.

Dark black door	Model	Capacity l	V	Consumption W/24 h	kg
50.918.01	NRX0035E	34	12/24	230	16
50.918.03	NRX0050E	46	12/24	222	17
50.918.05	NRX0060E	58	12/24	234	17
50.918.07	NRX0080E	78	12/24	304	20



▲ 50.913.20/30



▲ 50.913.40



▲ 50.913.20/30

DOMETIC drawer fridge

12/24V compressor drawer fridge. The cooling unit can be fitted up to 1.5 m away in case of limited depth. Stainless steel front.

Code	V	Capacity l	Temperature range	W	↔ mm		↔ depth mm	
					Width	Height	with compressor	without compressor
50.913.20	12/24	20	0° + 15°	36	438	250	565	422
50.913.30	12/24	30	-2° + 12°	36	440	250	730	560



50.913.40 Stainless steel frame for mounting of the 20- and 30-l version.