

SILENT ELECTRIC TOILETS



Electric toilet, with automatic load and waste. Very quiet operation. It needs 1 to 5 litres of water for every washing cycle. High-capacity centrifugal grinder to prevent clogging. Built-in Water Lock and anti-siphon valve. Designed to be connected to waste water tanks. Possibility of series mounting with a single pump and several solenoids. High-quality **ceramic** bowl. **Soft close plastic** board. Designed for "bidet kit" (except models 50.212.01-02-03-04). 38-mm Ø outlet. **Supplied with control panel 50.204.42.**

WC SILENT Space Saver - low bowl

SoftClose board. Control panel INCLUDED. Spray Nozzle flushing connection for faster and more effective cleaning with a high-pressure water jet over the entire surface of the WC.

Code	V	↔ mm	Self-priming pump for sea water suction OPTIONAL	Solenoid valve* OPTIONAL
50.210.12	12	330x420x360h	16.525.12	50.203.10

* OPTIONAL Electro-valve to connect the water intake to the W.C.



WC SILENT Compact - standard bowl

SoftClose board. Control panel INCLUDED.

Spray Nozzle washing fitting for faster and more effective cleaning at very high pressure on all the toilet bowl surface.

Code	V	↔ mm	Self-priming pump for sea water suction OPTIONAL	Solenoid valve* OPTIONAL
50.212.01	12	330x420x390h	16.525.12	50.203.10
50.212.02	24	330x420x390h	16.525.24	50.203.11

* OPTIONAL Electro-valve to connect the water intake to the W.C.



WC SILENT Comfort - big bowl

Control panel INCLUDED. Soft close board.

Spray Nozzle washing fitting for faster and more effective cleaning at very high pressure on all the toilet bowl surface.

Code	V	↔ mm	Self-priming pump for sea water suction OPTIONAL	Solenoid valve* OPTIONAL
50.212.03	12	365x460x385h	16.525.12	50.203.10
50.212.04	24	365x460x385h	16.525.24	50.203.11

* OPTIONAL Electro-valve to connect the water intake to the W.C.



New

SILENT Ultra Slim WC

Compact faired toilet bowl with specially designed **SLIM fixing base** suitable for mounting in confined spaces.

Ceramic bowl, soft-close seat, self-priming pump with suction/ drain function and macerator.

Carling control panel included with automatic cycle mode + manual mode **50.204.43**

Port connections: Inlet 19 mm (3/4"), Outlet 25 mm (1") or 38 mm (1 1/2")

Code	V	A	↔ mm				Self-priming pump for sea water suction OPTIONAL	Solenoid valve* OPTIONAL
			Height	Width	depth	Base		
50.316.12	12	30	410	355	480	225 x 272	16.525.12	50.203.10
50.316.24	24	16	410	355	480	225 x 272	16.525.24	50.203.11

* OPTIONAL Electro-valve to connect the water intake to the W.C.



50.204.43

