



Heaters, defrosters



Electronic forced-air heater

Connected to the onboard power, it heats the boat in a matter of minutes. Instant heating, automatic temperature control, secure and long lasting. Control symbols: on/off - fan only - heating - fan speed.


Code	V	Consumption
50.383.00	12	300 W



HEATER CRAFT bulkhead heater

The kit includes a heater, a 4 position panel switch, electrical cable and screws. The system exploits the engine cooling water to convey heat to the cabin. 3-speed motor, simple and fast mounting.

Code	V	Consumption at 3 speeds	Calorific yield
50.263.00	12	3,9 - 5,0 - 7,7 A	28.000 BTU/hour with water volume 11 l/min at 76° and with ambient temperature 15°




HEATER CRAFT 2-outlet centralized heater

Mounting is possible where needed. Two 75-mm Ø hoses connect to two adjustable outlets for bulkhead mounting. Same technical features as model 50.263.00. The kit includes a heater, a 4-position switch panel, mounting bracket, 3.6-m hose, 2 outlets, electrical cable and screws. Techniques of mod. 50.263.00. Kit includes heater + 4-position panel switch + mounting bracket + 3.60 m of pipe + 2 nozzles + electrical cable + screws.

Utilizes the engine's cooling water to transfer heat into the cabin. 3-speed motor, extremely simple and quick installation.

Code	V	Consumption at 3 speeds	Calorific yield
50.263.01	12	3,9 - 5,0 - 7,7 A	28.000 BTU/hour with water volume 11 l/min at 76° and with ambient temperature 15°



HEATER CRAFT 3-outlet centralized heater

Upgraded model similar to 50.263.01. Three hoses connect to three adjustable outlets. The kit includes a heater, a 4-position switch panel, mounting bracket, 5.4-m 75-mm Ø hose, 3 adjustable outlets, electrical cable and screws. The system exploits the engine cooling water to convey heat to the cabin. 3-speed motor, simple and fast mounting.

Power supply		Consumption at 3 speeds	Calorific yield
12 V	24 V		
50.263.02	50.263.03	4,4 - 5,8 - 8,4 A	40.000 BTU/hour with water volume 11 l/min at 76° and with ambient temperature 15°



▲ 50.263.11



▲ 50.263.08

Extra accessories Heater Craft

Code	Description	Roll m
50.263.06	"Y" joint for air canalisation (Ø mm 75)	-
50.263.11	Flexible pipe for air conduit Ø mm 75	12
50.263.08	Adjustable air outlet nozzle Ø 75 mm black	-



▲ 50.263.06

HEATER CRAFT



12V defroster/defogger unit

To be installed inside the control panel to defrost or defog the glass panes in wintertime.

Code	V	BTU/hr	No. of speed modes
50.264.12	12	1.706	1

