







Skin fittings

Skin fittings with 24-mm diameter intake hose. Made of AISI316 stainless steel.

Code	Туре	Tube Ø mm	Material
50.255.01	Standard	24	SS 316
50.255.02	With bent	24	SS 316
50.255.03	Slanted	24	SS 316







Autoterm Flow liquid heaters

AUTOTERM Flow liquid heaters are a versatile and compact solution for boats and vehicles, with a thermal power of 5 kW. Designed to heat cabins and interiors. Available for petroleum (12V) and diesel (12/24V) systems. The kit contains everything necessary for the installation of the boiler. Control panel 50.251.01 to be purchased separately to operate the boiler. To complete the installation, it will also be necessary to purchase the hot water circulation pipe (diameter 16mm type 17.740.16) and the local air distributions as needed.

The following accessories are included in the kit: Thermal insulation; Fuel pump clamp with rubber gasket; Fuel pump; Electrical wiring for the pump; Electrical wiring for control panels; Air intake hose with filter; 1 meter long exhaust pipe (optional adapters: 50.255.01/02/03); 5.5 meters of nylon fuel hose; Nylon fuel hose cover; Mounting bracket for the pump; Silencer with mounting kit; Heat cover for exhaust pipe; Electric liquid pump; Coolant hose connector; L-shaped exhaust pipe adapter; 2 meters of coolant hose.



Code	Model	Recommended for boats (m) Mediterra- Nordic nean climate	v	Power kW	Energy consump-	Fuel consump-	←		
					N.VV	tion (W)	tion (I/h)	mm	kg.
50.261.12	petrol	10-13	8-11	12	5	42	0.7	220x90x136	2.4
50.262.12	Diesel	10-13	8-11	12	5	42	0.62	220x90x136	2.4
50.262.24	Diesel	10-13	8-11	24	5	42	0.7	220x90x136	2.4

Speed

3

2



New

Heat exchangers (fan coil) for Autoterm Flow boiler

Heating capacity m³/h Outlets

110

347

236

314

 $Heat exchangers \ with integrated \ active fan for \ Autoterm Flow \ liquid \ heaters. \ They receive \ water \ produced \ by \ the \ boiler \ type$ 50.261.12 - 50.262.12/24 and distribute hot air. For versions without an integrated switch, any thermostat and/or switch with one or two speeds (type 50.266.30) can be connected.

Switch


Yes

Yes

no

no







12

12

12

12


Power kW

2 75

5.9

3.05

6.05



1

2

3x60mm



Thermosts

Yes

Yes

no

no

50.267.02

▲ 50.266.30

Type of mounting

bulkhead

bulkhead

recess

Remote³

fixation 4xØ3.8



▲ 50.266.02

