Sound-deadening quilt, heat-insulation up to 700°

It is a felt mat of glass fibre, coupled by quilting to two glass fabrics of 400 g, one of which is aluminized.
Stylish design, it is resistant to elevated mechanical strain. Particularly indicated as thermo acoustic isolator.

Code	Thickness mm	Roll
65.093.00	10	1 m x 10 m

Fits perfectly to the walls and can be glued or fixed with washers 65.098.00. Price per coil.

65.098.00 *OPTIONAL washers*

VETROTEX fibreglass mat

Sound-deadening, noise-insulating, fitted with aluminized fibreglass on the external side. Used as **anti-heat** covering on exhaust pipes, heat exchangers and on any piping needing to be insulated. Price by the single roll.

Code	Thickness mm	Fireproof	Roll
65.096.00	10	class 1	20 x 500 cm

Adhesive aluminium tape roll

designed to finish sound-deadening noise-insulating panels 65.094.00 after they are modelled and mounted

Code	Roll m	Height mm
65.095.00	50	50

CIBA marine glue

Made with phenolic resins, dark red colour, fitted with powder catalyst. It's the most powerful glue in the world, used to glue wood, resin, polyester, metals, etc.

Code	Package	Type-approval
65.225.11	500 g	RINA

Self-extinguishing glue for sound-insulating/sound-deadening panels

Sound-insulating glue that optimizes the performance of the panels it is applied to.

Code	Package	Type-approval	Yield gr/mq
65.100.02	0.750 l	RINA	350/400

Plastic toothed washers

OSCULATI

For fixing sound-deadening panels onto ceilings or bulkheads. Screws not included.

Code	Ø mm	Hole mm	Package
65.098.00	50	3	250 pcs.
65.098.40	50	3	40 pcs. (blister)

ADEBOND professional cianoacrylic bonding

It sticks immediately metal, plastic, rubber, wood, leather, artificial leather, etc... Dispenser package.

Code	
65.236.21	50

NEW

Lubricants and DURALAC

Duralac Green

Renewed version of the original Duralac, it is a plastic insulator and sealant used to prevent galvanic corrosion at the contact point between two different metals, such as: aluminum cleats fixed with stainless steel screws, aluminum or brass winches fixed with stainless steel bolts, stainless steel accessories for shafts fixed on the shaft itself (in aluminum) with rivets or screws, bollards coupled with studs of different metal.
It is a yellow, chrome-free, durable and flexible paste that is interposed between two metals during coupling.
Applied with a brush and should not be diluted.

◢ 65.750.02

◢ 65.750.01/03

Code		Version	Package ml
65.750.02	New	Tube	115
65.750.01		Tin	250
65.750.03	New	Tin	1000