Air vents for heat-shrinking covering

Good protection against the ingress of unwanted external agents to prevent condensate, mould and bad odours

Code	Description
46.188.01	Piercieng triangular vent
46.188.02	Adhesive round vent

46.188.02

Rafale Black Edition + propane gas shrinkforming gun

Propane gas heat gun designed for polyethylene shrinking. Weighing 1.170 kg, the ergonomic and quiet Rafale Black Edition (88 dB at 1 m - 85 dB) has been engineered to minimise user fatigue even after extended periods of use. It has an air consumption of 48 to 72.2 m^3/h and a flow rate of 3.2 to 4.8 kg/h. The injector diameter is 1.3 mm, and the head can rotate 360° for use in any position. The aluminium burner with double protection ensures maximum safety while remaining warm regardless of duration and intensity of use. Power adjustment options range from 44 to 66 kW/h. Supplied with a carrying case and complete with: 8 m of NF EN 559 rubber hose, 1 instruction manual, 1 pair of gloves, and 1 heat reflector. CE marking No. 4450.

Code	Description
46.177.00	Propane gas shrinkforming gun (faucet not included)
46.177.10	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Algeria, Belgium, Spain, France, Hungary, Luxembourg, Morocco, Holland, Poland, Portugal, Czech Republic, Switzerland, Tunisia.
46.177.12	Pressure regulator and pressure gauge for shrinkforming gun with fitting for UK, Canada, Ireland.
46.177.13	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Italy and Greece.
46.177.15	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Turkey.
46.177.16	Pressure regulator and pressure gauge for shrinkforming gun with fitting for Russia.

To use the gun, also order the suitable fitting (to be chosen depending on the country of use).

46.177.00

46.177.10/12/13/15/16

Gas cylinder trolley

The cylinder trolley is easy to assemble, lightweight, foldable, and manageable.
Comes with straps that serve to secure the cylinder during transport and a special support for the heat gun (code **46.177.00**).

Code	Max load kg	Wheel Ø mm	⟷ mm		kg
			open (LxWxH)	closed (LxWxH)	
46.177.30	13	145	106x45x40	60x40x26	7.5

Heat-shrinking polyethylene adhesive tape

To join, seal and repair heat-shrinking film. Also used when installing fixtures such as doors, openings, vents, etc. Resistant to abrasion, UV rays, weather and chemical agents.

Code	Width mm	Length mm
46.186.00	50	33
46.186.01	96	55

Polyethylene doors and openings.

To enable access to the structure.

Code	Outside mm	Closing
46.187.01	1750x750	Zip