


## ► Ancore



OSCULATI




## Ancora Trefoil® in acciaio fuso e zincato a caldo

Ad interramento progressivo.

Codice		A mm	B mm	C mm
01.110.02	2	175	358	210
01.110.05	5	273	469	310
01.110.07	7,5	298	531	360
01.110.10	10	320	583	380
01.110.13	13	330	630	410
01.110.15	15	335	655	405
01.110.20	21	395	701	470
01.110.30	32	410	800	560
01.110.50	50	470	980	660
01.110.80	80	560	1100	720



OSCULATI



## Ancora Trefoil® in acciaio inox AISI 316 lucidato a specchio


AISI 316

Finitura di ottima qualità, data dal fatto che le nostre Trefoil® inox sono fabbricate in **microfusione** e lavorate a mano, con risultati estetici e dimensionali perfetti.

Codice		A mm	B mm	C mm
01.109.25	2,5	170	357	235
01.109.05	5	240	470	320
01.109.07	7,5	270	540	360
01.109.10	11	310	590	385
01.109.15	15	335	645	450
01.109.20	20	355	660	475
01.109.30	30	410	815	560
01.109.50	50	495	1000	665



OSCULATI



## Ancora Trefoil® versione pieghevole in acciaio fuso e zincato a caldo

PATENT

Abbina l'enorme tenuta delle Trefoil® con la praticità delle ancore pieghevoli facilmente stivabili a bordo.

Codice		A mm	B mm	C mm
01.104.05	5	240	469	315
01.104.07	7,5	273	531	361

