



Treccia poliestere Square Line ad alta tenacità a 8 fusi passo lungo

Indicata specialmente per **cime d'ormeggio**.
Molto facile da impiombare, robusta e maneggevole.

Bianco	Blu	Ø mm	Carico di rottura kg	m
06.448.12	06.458.12	12	2000	200
06.448.14	06.458.14	14	2500	200
06.448.16	06.458.16	16	3000	100
06.448.18	06.458.18	18	3900	100
06.448.20	06.458.20	20	4600	100
06.448.22	06.458.22	22	5500	100
06.448.24	06.458.24	24	6600	80



▲ 06.467.xx



▲ 06.468.xx



▲ 06.469.xx

Doppia treccia a 16 fusi in morbido poliestere ad alta tenacità

Adatta per ormeggio e scotte.

Colore		Colore			Ø mm	m
Bianco	Carico di rottura kg	Blu	Nero	Carico di rottura kg		
06.467.05	350	06.468.05	06.469.05	350	5	200
06.467.06	500	06.468.06	06.469.06	500	6	200
06.467.08	800	06.468.08	06.469.08	720	8	200
06.467.10	1440	06.468.10	06.469.10	1200	10	200
06.467.12	2040	06.468.12	06.469.12	1800	12	200
06.467.14	2300	06.468.14	06.469.14	2000	14	100
06.467.16	2840	06.468.16	06.469.16	2500	16	100
06.467.18	4460	06.468.18	06.469.18	4000	18	100
06.467.20	5250	06.468.20	06.469.20	4500	20	100
06.467.24	7950	06.468.24	06.469.24	6800	24	100



OSculati

Cima di ormeggio impiombata ad alta tenacità

In poliestere alta tenacità, a **3 capi**, complete di redance inox e **impiombatura fatta a mano**.

Colore		Colore			Ø mm	Lunghezza m
Bianco	Carico di rottura kg	Blu	Nero	Carico di rottura kg		
06.443.10	1300	-	-	-	10	6
06.443.11	2000	06.443.31	06.443.01	1600	12	6
06.443.12	2000	06.443.32	06.443.02	1600	12	9
06.443.13	2700	06.443.33	06.443.03	2150	14	8
06.443.14	2700	06.443.34	06.443.04	2150	14	12
06.443.15	3600	06.443.35	06.443.05	3000	16	8
06.443.16	3600	06.443.36	06.443.06	3000	16	12
06.443.19	5200	06.443.39	06.443.07	4200	20	8
06.443.20	5200	06.443.40	06.443.08	4200	20	12
06.443.24	6750	06.443.44	06.443.09	5500	24	15
06.443.28	8700	06.443.48	06.443.58	7000	28	15



▲ 06.443.24



▲ 06.443.04



▲ 06.443.44



▲ 06.443.44



▲ 06.443.04



▲ 06.443.24

Cima di ormeggio impiombata ad alta tenacità

In poliestere **alta tenacità 8 capi** "Square Line" 06.458.xx colore blu, complete di redance inox e **impiombatura fatta a mano**.

Codice	Ø mm	Lunghezza m
06.443.50	16	12 (reale corda 12,50)
06.443.52	20	12 (reale corda 12,50)
06.443.54	24	15 (reale corda 15,50)

