

Cima di ormeggio impiombata ad alta tenacità doppia treccia

In **doppia treccia poliestere alta tenacità** con redancia inox e impiombatura fatta a mano.

Colore		Colore		Ø mm	Lunghezza m
Bianco	Carico di rottura kg	Blu	Nero		
06.443.70	1440	06.443.80	06.443.90	10	6
06.443.71	2040	06.443.81	06.443.91	12	7
06.443.72	2300	06.443.82	06.443.92	14	9
06.443.73	2840	06.443.83	06.443.93	16	11
06.443.74	5250	06.443.84	06.443.94	20	12
06.443.75	-	06.443.85	06.443.95	24	15



OSculati



Cima di ormeggio ad alta tenacità con occhio

Doppia treccia poliestere **alta tenacità** con occhio impiombato a mano.

Colore		Colore		Ø mm	Lunghezza m	Ø anello cm
Bianco	Carico di rottura kg	Blu	Nero			
06.444.30	1400	06.444.41	06.444.90	10	6	20
06.444.32	2040	06.444.43	06.444.92	12	7	20
06.444.34	2300	06.444.45	06.444.94	14	9	20
06.444.36	2840	06.444.47	06.444.96	16	11	20
06.444.38	-	06.444.48	06.444.98	20	12	20
06.444.39	7950	06.444.49	06.444.99	24	15	20



OSculati



Cima per ancora in treccia di poliestere con anima in piombo per i primi 10 m

Terminale con redancia e impiombatura fatta a mano.
Fornite confezionate con elegante sacchetto in nylon / cordino Blu.

Codice	Ø mm	Lunghezza m	Lunghezza parte con piombo m	Peso piombo kg	Peso totale kg
06.446.10	10	30	10	3	5
06.446.12	12	30	10	4	7,5



Spezzoni di treccia in poliestere

Di prima qualità, colore bianco con segnalino, preconfezionati con **impiombatura e redance in nylon**.

Codice	Ø mm	Lunghezza m	Codice	Ø mm	Lunghezza m
06.442.01	8	15	06.442.04	10	15
06.442.02	8	30	06.442.05	10	30
06.442.03	8	40	06.442.06	10	40



Treccia/piattina in polipropilene a 32 fusi

Studiata appositamente per il fissaggio dei parabordi.
Fabbricata senza anime e facilissima da impiombare senza alcuna conoscenza specifica.

Bianco	Blu navy	Nero	Ø nominale mm	Piattina mm	m
06.444.10	06.444.20	06.444.80	10	3,3 x 18	50
06.444.11	06.444.21	06.444.81	14	4,5 x 20	50
06.444.12	06.444.22	06.444.82	18	5,6 x 25	50

