

OSCOLATI



▲ 11.050.01/02; 11.051.01/2



▲ 11.052.02



▲ 11.048.01; 11.049.01




▲ 11.048.02; 11.049.02




▲ 11.050.03; 11.051.03




▲ 11.050.04; 11.051.04



▲ 11.052.02



▲ 11.050.xx; 11.051.xx



▲ 11.049.01/02



▲ 11.048.xx; 11.049.xx



▲ 11.050.xx

Luci di via a LED Sea-Dog in acciaio inox

AISI 316

Certificate COLREG72 e ABYC-C5. Completamente in AISI 304 e corpo in policarbonato.

Tipo	Versione per scafi fino a 12 m - 12 V	Versione per scafi fino a 20 m - 12/24 V	Fissaggio
112,5° sinistro	11.050.01	11.051.01	Sup piano
112,5° destro	11.050.02	11.051.02	Sup piano
112,5° + 112,5° bicolore	11.050.03	11.051.03	Sup piano
225° bianco	11.050.04**	11.051.04**	Sup piano
112,5° sinistro	11.048.01	11.049.01	A parete
112,5° destro	11.048.02	11.049.02	A parete
135° poppa	-	11.052.02*	A parete

* 11.052.02 Solo 12 V

** Non omologati

OSCOLATI

Luci di via EVOLED con sorgente luminosa a LED a basso consumo

LED

Per imbarcazioni fino a 20 m, certificate COLREG72 e ABYC-C5.

Tipo	Corpo in policarbonato bianco	Corpo in policarbonato nero	Corpo acciaio inox lucido	V	W
112,5° sinistro + 112,5° destro	11.039.01	11.039.02	11.039.21	12	1
135° poppa	11.039.14	-	11.039.24	12	1




▲ 11.039.01


▲ 11.039.21



▲ 11.039.14



▲ 11.039.14/24



▲ 11.039.01/21/02



▲ 11.039.02



▲ 11.039.24



▲ 11.039.14



▲ 11.039.01