





▲ Disegno 1




▲ Disegno 2



▲ Disegno 3



▲ Disegno 4



▲ Disegno 5

Barilotto scambiatore calore

Zinco con filetto per impianto di raffreddamento.

Codice	Ø x Lunghezza mm	Filetto "	Motore	Disegno	Rif. originale
43.228.29	14x26+7	liscio Ø 12 mm	Caterpillar	3	Serie 3208
43.228.30	10x55+12	1/4	Caterpillar	1	6L2283
43.229.13	9x35+11	1/4	Caterpillar	1	116-7011
43.228.00	12x40+10	3/8	Caterpillar/Bukh	1	6L-2280
43.228.91	14x32+12	5/16"	Caterpillar	1	6L-2284
43.229.08	10x38+10	7/16	Caterpillar	1	6L-3104
43.229.09	16x41+9	7/16	Caterpillar	1	7E-5076
43.228.50	30x64+20	3/4	Caterpillar	1	-
43.229.02	14x20+10	M8	VM	1	-
43.229.03	14x40+10	M8	VM	1	-
43.229.04*	10x17+9	16x1,5	Nanni/Mercedes	2	-
43.229.06*	8x30	1/4 gas	Isoterm	4	-
43.229.01	12x35+Vok	M5	Bukh	1	-
43.541.00*	10x40+18	3/8	Caterpillar	5	-
43.548.00*	16x52+22	1/2"	GM/Caterpillar	5	-
43.545.00*	20x80+29	3/4	GM	5	-

*Con testa ottone.



▲ Disegno 1



▲ Disegno 3

Barilotti AIFO-FPT

Codice	Ø x lunghezza mm	Filetto	Motore	Disegno	Rif. originale
43.229.05	14x26+8	Liscio Ø 12 mm	AIFO-FPT	3	8105277
43.229.07	13x26+7	Liscio Ø 10 mm	AIFO-FPT	3	8105277
43.229.21	13x26+8	Liscio Ø 10,1 mm	AIFO-FPT	3	8105277/B
43.229.22	10x18+8	Liscio Ø 7 mm	AIFO-FPT	3	8109743
43.229.23	14x40+10	M8	AIFO-FPT	1	-



▲ Disegno 1



▲ Disegno 3

Barilotti Cummins

Codice	Ø x lunghezza mm	Filetto	Motore	Disegno	Rif. originale
43.229.10	16x50+10	7/16"	Cummins	1	-
43.229.26	16x31+13	3/8"	Cummins	1	-
43.229.27	10x20+8	M6	Cummins	1	-

Barilotti Yanmar

Codice	Ø x lunghezza mm	Filetto	Motore	Disegno	Rif. originale
43.228.10	12x30+11	3/8"	Yanmar	1	68241
43.542.00	20x40	M8	Yanmar	1	27210-200300
43.229.40	12x32	3/8"	Yanmar	1	-
43.229.41	16x50+10	7/16"	Yanmar	1	-
43.229.42	New 12x30+10	3/8"	Yanmar	1	-
43.229.43	New 15x20+9	M8	Yanmar	1	-
43.229.44	New 12,70x38,10+10	3/8"	Yanmar	1	-

Anodo a saponetta

Per timoni o flaps.

Codice	l mm	g
43.701.00	85x47x20(H)	300
43.702.00	145x41x23(H)	550

