

## Cime MARLOW da ormeggio a 3 capi in poliestere

## ORMEGGIO DOCKING

In poliestere alta tenacità a 3 capi a gherlino.

Marlow®

| Bianco    | Nero      | Blu       | Ø mm | Carico di rottura kg | m   |
|-----------|-----------|-----------|------|----------------------|-----|
| 06.472.06 | 06.482.06 | 06.484.06 | 6    | 951                  | 200 |
| 06.472.08 | 06.482.08 | 06.484.08 | 8    | 1465                 | 200 |
| 06.472.10 | 06.482.10 | 06.484.10 | 10   | 2570                 | 200 |
| 06.472.12 | 06.482.12 | 06.484.12 | 12   | 3170                 | 200 |
| 06.472.14 | 06.482.14 | 06.484.14 | 14   | 3930                 | 100 |
| 06.472.16 | 06.482.16 | 06.484.16 | 16   | 4766                 | 100 |
| 06.472.18 | 06.482.18 | 06.484.18 | 18   | 6600                 | 100 |
| 06.472.20 | 06.482.20 | 06.484.20 | 20   | 9230                 | 100 |
| 06.472.24 | 06.482.24 | 06.484.24 | 24   | 11210                | 100 |
| 06.472.28 | 06.482.28 | 06.484.28 | 28   | 14640                | 100 |



## Doppia treccia, 16 fusi da Ø mm 5 a 16, 24 fusi da Ø mm 18 a 24, in morbido poliestere ad alta tenacità

Adatta per ormeggio e scotte. Venduta a bobina.

## ALTA TENACITÀ / HIGH-STRENGTH

| Colore    |                      |           |           |                      | Ø mm | m   |
|-----------|----------------------|-----------|-----------|----------------------|------|-----|
| Bianco    | Carico di rottura kg | Blu       | Nero      | Carico di rottura kg |      |     |
| 06.467.05 | 350                  | 06.468.05 | 06.469.05 | 350                  | 5    | 200 |
| 06.467.06 | 500                  | 06.468.06 | 06.469.06 | 500                  | 6    | 200 |
| 06.467.08 | 800                  | 06.468.08 | 06.469.08 | 720                  | 8    | 200 |
| 06.467.10 | 1440                 | 06.468.10 | 06.469.10 | 1200                 | 10   | 200 |
| 06.467.12 | 2040                 | 06.468.12 | 06.469.12 | 1800                 | 12   | 200 |
| 06.467.14 | 2300                 | 06.468.14 | 06.469.14 | 2000                 | 14   | 100 |
| 06.467.16 | 2840                 | 06.468.16 | 06.469.16 | 2500                 | 16   | 100 |
| 06.467.18 | 4460                 | 06.468.18 | 06.469.18 | 4000                 | 18   | 100 |
| 06.467.20 | 5250                 | 06.468.20 | 06.469.20 | 4500                 | 20   | 100 |
| 06.467.24 | 7950                 | 06.468.24 | 06.469.24 | 6800                 | 24   | 100 |



▲ 06.467.xx



▲ 06.468.xx



▲ 06.469.xx



▲ 06.467.xx

▲ 06.468.xx

▲ 06.469.xx

## Treccia poliestere Square Line ad alta tenacità a 8 fusi passo lungo

Indicata specialmente per cime d'ormeggio. Molto facile da impiombare, robusta e maneggevole. Venduta a bobina.

| Bianco    | Nero      | Blu       | Ø mm | Carico di rottura kg | m   |
|-----------|-----------|-----------|------|----------------------|-----|
| 06.448.12 | 06.478.12 | 06.458.12 | 12   | 2000                 | 200 |
| 06.448.14 | 06.478.14 | 06.458.14 | 14   | 2500                 | 200 |
| 06.448.16 | 06.478.16 | 06.458.16 | 16   | 3000                 | 100 |
| 06.448.18 | 06.478.18 | 06.458.18 | 18   | 3900                 | 100 |
| 06.448.20 | 06.478.20 | 06.458.20 | 20   | 4600                 | 100 |
| 06.448.22 | -         | 06.458.22 | 22   | 5500                 | 100 |
| 06.448.24 | 06.478.24 | 06.458.24 | 24   | 6600                 | 80  |



## Cima ormeggio 3 capi impiombata con redancia

In poliestere alta tenacità, con redancia inox e impiombatura fatta a mano.

| Bianco    | Carico di rottura kg | Blu       | Nero      | Carico di rottura kg | Ø mm | Lunghezza m |
|-----------|----------------------|-----------|-----------|----------------------|------|-------------|
| 06.443.10 | 1300                 | -         | -         | -                    | 10   | 6           |
| 06.443.11 | 2000                 | 06.443.31 | 06.443.01 | 2000                 | 12   | 6           |
| 06.443.12 | 2000                 | 06.443.32 | 06.443.02 | 2000                 | 12   | 9           |
| 06.443.13 | 2700                 | 06.443.33 | 06.443.03 | 2700                 | 14   | 8           |
| 06.443.14 | 2700                 | 06.443.34 | 06.443.04 | 2700                 | 14   | 12          |
| 06.443.15 | 3600                 | 06.443.35 | 06.443.05 | 3600                 | 16   | 8           |
| 06.443.16 | 3600                 | 06.443.36 | 06.443.06 | 3600                 | 16   | 12          |
| 06.443.19 | 5200                 | 06.443.39 | 06.443.07 | 5200                 | 20   | 8           |
| 06.443.20 | 5200                 | 06.443.40 | 06.443.08 | 5200                 | 20   | 12          |
| 06.443.24 | 6750                 | 06.443.44 | 06.443.09 | 6750                 | 24   | 15          |
| 06.443.28 | 8700                 | 06.443.48 | 06.443.58 | 8700                 | 28   | 15          |



▲ 06.443.44

▲ 06.443.04

▲ 06.443.24

OSCULATI



▲ 06.443.24



▲ 06.443.04



▲ 06.443.44



## Cima di ormeggio impiombata ad alta tenacità

In poliestere alta tenacità 8 capi "Square Line" 06.458.xx colore blu, complete di redance inox e impiombatura fatta a mano.

| Codice    | Ø mm | Lunghezza m            |
|-----------|------|------------------------|
| 06.443.50 | 16   | 12 (reale corda 12,50) |
| 06.443.52 | 20   | 12 (reale corda 12,50) |
| 06.443.54 | 24   | 15 (reale corda 15,50) |

